



## **RF 15-35mm F2.8 L IS USM**

- High Image Quality and Bright f/2.8 Wide-angle Zoom RF L Lens.
- Optical Image Stabilization of up to 5 Stops\* of Shake Correction.
- High Speed, Smooth and Quiet Auto Focus with Nano USM.
- Minimum Focusing Distance of 0.92 ft./0.28m.
- Control Ring for Direct Setting Changes.
- 12 pin Communication System.
- Three Aspherical Elements and Two UD Elements.
- Dust- and Weather-resistant with Flourine Coating.
- Air Sphere Coating (ASC) Minimizes Lens Flare and Ghosting.

### **PRODUCT OVERVIEW**

Expand your field of view with the RF 15-35mm F2.8 L IS USM lens. This wide-angle, L-series lens is a dynamic addition to the EOS R series line-up, offering a bright f/2.8 maximum aperture and 15-35mm focal length that helps capture landscapes, architecture and other wide-angled subjects in full view. Equipped with Canon's Nano USM technology for quiet and smooth focusing, and up to 5 stops\* of shake correction, the RF 15-35mm F2.8 L IS USM allows for clear shots in a variety of lighting conditions — even at night or in dark settings. Experiment with different angles and perspectives, with a minimum focusing distance of 0.92 ft./0.28 m. For reliable performance during tricky weather conditions, this lens is expertly sealed around its panels, switch and lens mount to prevent water and dust from entering into the lens. When it comes to raising your photography game, turn to the RF 15-35mm F2.8 L IS USM to deliver impressive results.

### **PRODUCT SPECIFICATIONS**

<b>Model Name</b>	RF1535/2.8LU
<b>Description</b>	RF15-35/2.8L IS USM
<b>Item Number</b>	3682C002[AA]
<b>Availability Date</b>	August, 2019
<b>Country of Origin</b>	Japan
<b>UPC Code</b>	013803323511



### **COMPATIBLE SUPPLIES & ACCESSORIES**

<b>Lens Case</b>	Lens Case LP-1222
<b>Lens Hood</b>	Lens Hood EW-88F
<b>Lens Caps</b>	Lens Cap E-82II Lens Dust Cap RF

### **DISCLAIMERS**

\* Based on CIPA (Camera & Imaging Products Association) standards. Testing performed at a focal length of 35mm using the EOS R camera.

### **TECHNICAL SPECIFICATIONS**

<b>Focal Length &amp; Maximum Aperture</b>	15-35mm f/2.8
<b>Minimum Focusing Distance</b>	0.92 ft./0.28 m
<b>Maximum Magnification</b>	0.21x (at 35mm)
<b>Lens Construction</b>	16 elements in 12 groups
<b>Special Elements</b>	3 Aspherical lenses, 2 UD lenses
<b>Filter Size Diameter</b>	Ø82 mm
<b>Aperture Blades</b>	9 (circular)
<b>IS (CIPA Standard Correction Effect)</b>	5 stops (When using the EOS R camera with a 35mm focal length)
<b>Focus Drive System</b>	Nano USM
<b>Minimum Overall Length</b>	Approx. 4.99 in. / 126.8 mm
<b>Maximum Diameter</b>	Approx. Ø3.48 in. / 88.5 mm
<b>Weight</b>	Approx. 1.85 lbs. / 840 g