



## Specifications

### PH-2 Specifications

#### Connector Termination

PH-2 A4F: XLR 4-pin Female

PH-2 A4M: XLR 4-pin Male

PH-2 PT: Stripped Wire

#### Type

PH-2 A4F: Dual Sided Monaural

PH-2 A4M: Dual Sided Monaural

PH-2 PT: Dual Sided

#### Mic Type

Dynamic Noise-Canceling

#### Mic Sensitivity

-65dBV/Pa @ 1cm

#### Mic Frequency Range

200Hz–6kHz

#### Mic Impedance

150Ω

#### Speaker Sensitivity

95dB SPL @ 1kHz, 1mW

#### Speaker Frequency Range

100Hz–10kHz

#### Speaker Impedance

PH-2 A4F: 150Ω

PH-2 A4M: 150Ω

PH-2 PT: 300Ω per side

#### Weight

13 oz (368.54 g), not including cord

#### Cord Length

6.0 ft ±2 in (1.83 m ±5.08 cm)

### PH-3 Specifications

#### Connector Termination

PH-3 A5F: XLR 5-pin Female

PH-3 A5M: XLR 5-pin Male

#### Type

PH-3 A5F: Dual Sided Stereo

PH-3 A5M: Dual Sided Stereo

#### Mic Type

Dynamic Noise-Canceling

#### Mic Sensitivity

-65dBV/Pa @ 1cm

#### Mic Frequency Range

200Hz–6kHz

#### Mic Impedance

150Ω

#### Speaker Sensitivity

95dB SPL @ 1kHz, 1mW

#### Speaker Frequency Range

100Hz–10kHz

#### Speaker Impedance

300Ω per side

#### Weight

13 oz (368.54 g), not including cord

#### Cord Length

6.0 ft ±2 in (1.83 m ±5.08 cm)

## Order Information

PH-2 A4F • Dual-Sided Headset with Flexible Dynamic Boom Mic and A4F Connector

PH-2 A4M • Dual-Sided Headset with Flexible Dynamic Boom Mic and A4M Connector

PH-2 PT • Dual-Sided Headset with Flexible Dynamic Boom Mic, and Pigtail Termination

PH-3 A5F • Dual-Sided Headset with Flexible Dynamic Boom Mic and A5F Connector

PH-3 A5M • Dual-Sided Headset with Flexible Dynamic Boom Mic and A5M Connector

63801001 • Head Pad Assy

63444001 • SPP C3 Ear Cushion, Black, PH1/2/3, HD-3

35772000 • SPP Cover Cushion CC-1, PH1/2/3, HD-3

The specification information is preliminary and is subject to change without notification.  
Brand names mentioned are the property of their respective companies.