



CM-C54T | CM-C56T

CEILING LOUDSPEAKER

Offering crystal-clear audio, a discreet embedded design, and a host of practical features, the CM-C54T and CM-C56T are ideal for installations at hotels, restaurants, bars, commercial spaces and other locations where superior sound and aesthetics are key.

KEY FEATURES

- 2 way coaxial speaker
- 16 Ω impedance
- Protective steel-back can
- One-touch spring-loaded ceiling mounting tab
- The slide-lock mechanism on the grille
- UL2043 / UL1480A compliant for United States and Canada
- Also compatible with XY Series
- Paintable grills

APPLICATIONS

Hotels, restaurants, bars, commercial spaces and other locations where superior sound and aesthetics are key.

SPECIFICATIONS

| | CM-C54T-W | CM-C54T-K | CM-C56T-W | CM-C56T-K |
|---------------------------------------|---|-------------------------------|------------------------------------|-------------------------------|
| Frequency response (- 10 dB, Typical) | 85 Hz ~ 20 kHz | | 82 Hz ~ 20 kHz | |
| Dispersion | 120° | | 90° | |
| Sensitivity (1W / 1m) | 86 dB | | 88 dB | |
| Nominal Impedance | 16 Ω | | | |
| Power Handling | 30 W / 60 W | | 60 W / 120 W | |
| Transformer taps | 70 V | 30 W / 15 W / 7.5 W / 3.7 W | | 60 W / 30 W / 15 W / 7.5 W |
| | 100 V | 30 W / 15 W / 7.5 W | | 60 W / 30 W / 15 W |
| Driver configuration | LF | 4-inch (102-mm) cone | | 6.5-inch (165-mm) cone |
| | HF | 3/4-inch (20-mm) dome tweeter | | 3/4-inch (20-mm) dome tweeter |
| Connector | Euroblock (4 pin) × 1 (input: +/-, loop-thru: +/-) | | | |
| Color | White | Black | White | Black |
| Dimensions (W x H) | 240 x 210 mm (9.45 x 8.27 inches) | | 278 x 211 mm (10.94 x 8.31 inches) | |
| Weight (1 piece) | 2.6 kg | | 3.5 kg | |
| Accessories | C-ring Tile bridge 4-pin Euroblock connector Template for cutting the ceiling hole | | | |
| Packaging Type | 2 pieces per package | | | |

