

IP TESTER



The IP TESTER is a unique mobile service tool developed by Elation to test the integrity of any compatible IP-rated lighting fixture such as Elation's PROTEUS series fixtures, after being opened for lamp and gobo replacement or repair. Unlike other IP fixture test devices currently available in the market, Elation's IP TESTER has been designed to test for both Vacuum and Pressure leaks.

Features include an easy to carry rugged flight case, an easy to navigate 6-button LCD control menu display, testing progress bars to indicate remaining test time, preloaded Elation IP-rated lighting fixture model test presets, manual test setup for any compatible non-Elation models, fixture serial number input to keep track of fixtures tested, Micro SD card slot to store test reports, and a USB connection for PC software control.

The IP TESTER includes a 3-5 ft (0.9-1.5m) coiled air hose with quick-connect fitting, threaded M12 brass nozzle with push-to-connect fitting, 2 M12 x 1.5 nylon bolts, 6ft (1.8m) USB cable, 5ft (1.5m) Locking Power Cord, a Micro SD Card, and an easy to carry rugged case.

Please contact Elation Service for more information.

FEATURES

Mobile IP Fixture Vacuum and Pressure Tester

Developed by ELATION PROFESSIONAL

Compatible with any IP Fixture like Elation's PROTEUS Series

Preloaded Elation IP Rated Lighting Fixture Test Presents

Manual and Auto Testing Modes

Easy to navigate LCD Control Menu Display

Fixture Serial Number Input for Tracking Test Results

Micro SD Card to Store Test Results

USB Connection for PC Software Control (Windows)

Easy To Carry Rugged Case



ELATION | IP TESTER™ | Product Specification Sheet

Specifications are subject to change without notice ©Elation Professional 11/06/18

Elation Professional USA | 6122 S. Eastern Ave. | Los Angeles, CA. 90040
323-582-3322 | 323-832-9142 fax | www.elationlighting.com | info@elationlighting.com

Elation Professional B.V. | Junostraat 2 | 6468 EW Kerkrade, The Netherlands
+31 45 546 85 66 | +31 45 546 85 96 fax | www.elationlighting.eu | info@elationlighting.eu

PRODUCT SPECIFICATIONS

CONTROL / CONNECTIONS

- LCD Control Menu Display
- PC SOFTWARE (Win 7, 8, 8.1, 10)
- Air In/Out Vent
- Quick-Release Air Hose Fitting
- Micro SD Card Slot
- USB B Port
- Locking Power Cable In

SIZE / WEIGHT

- Length: 16.5" (419.1mm)
- Width: 6.5" (165.1mm)
- Vertical Height: 14.25" (362mm)
- Weight: 15.4 lbs. (7.0kg)

ELECTRICAL

- AC 100-240V - 50/60Hz
- 40W Max Power Consumption

INCLUDED ITEMS

- 3-5ft (0.9-1.8m) Air Hose with Quick-Connect Fitting
- M12 Threaded Brass Nozzle with Push-to-Connect Fitting
- (x2) M12 x 1.5 Orange Colored Nylon Bolt
- 6ft (1.8m) USB Cable
- 5ft (1.5m) Locking Power Cable
- Micro SD Card (4GB min)

ORDERING INFORMATION

IP TESTER	IP TESTER
50501990323	3-5ft Coiled Air Hose/Quick-Connect Fitting
9900010723	M12 Threaded Brass Nozzle/Push-to-Connect Fitting
TBD	M12 Orange Colored Nylon Bolt
NEU088	3 ft. (1m) Locking Power Link Cable

