

# ColorBlast IntelliHue Powercore gen4

Customizable exterior LED flood luminaire with intelligent color light

Date: \_\_\_\_\_  
 Type: \_\_\_\_\_  
 Firm Name: \_\_\_\_\_  
 Project: \_\_\_\_\_

ColorBlast IntelliHue Powercore high-performance LED luminaires combine white and rich, saturated, color and color-changing effects with simplified installation. ColorBlast IntelliHue Powercore offers a range of accessories that allow for customizable beam angles for floodlighting, spotlighting, wall washing, and grazing, along with the efficiency and cost-effectiveness of Powercore technology in a rugged die-cast aluminium housing.



- Expands customization with a wide range of new accessory options. In addition to the native 10° lens, five different spread lenses can customize the luminaire to produce 20°, 40°, 60°, 80°, and 10° x 40° (asymmetric) beam angles. Three housing color choices (black, gray, and white) – plus the option to add or combine a louver, rock guard, full glare shield, and half glare shield – create new aesthetic possibilities for designers and architects.
- Improves color consistency between all LED luminaires in a family with Chromasync technology. During the manufacturing process a calibrated light measurement device creates an algorithm to define a common color gamut for an entire family of LED luminaires. When Chromasync is enabled, color consistency between luminaires is achieved without having to manually adjust color points on each luminaire.

[Product page](#)

Beam Angle	10°, 20°, 40°, 60°, 80°, 10° x 40°
Lumens All Channels Full On*	2,012 to 2,434
Efficacy (lm/W) All Channels Full On	39.3 to 50.8
LED Channels	Red/Green/Blue/Mint White

Input Voltage	100 to 277 VAC, auto-ranging, 50/60 Hz via Data Enabler Pro
Power Consumption	50 W
Weight	3.9 kg (8.2 lb)
Housing Material	Die-cast aluminium, powder-coated finish
Approbations	UL/cUL, FCC Class A, CE, PSE, CQC, RCM
Environment	Dry/Damp/Wet Location, IP66
Applications	Flood Lighting, Spot Lighting, Wall Washing

## Specification Sheets

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
<a href="#">100 – 277 VAC, 10° Native (no spread lens), Black Housing, UL/CE/CQC</a>	10°	2,434	50.8	423-000011-01	912400130372		
<a href="#">100 – 277 VAC, 10° Native (no spread lens), Gray Housing, UL/CE/CQC</a>	10°	2,434	50.8	423-000011-04	912400133545		
<a href="#">100 – 277 VAC, 10° Native (no spread lens), White Housing, UL/CE/CQC</a>	10°	2,434	50.8	423-000011-00	912400130371		
<a href="#">100 – 277 VAC, 20° Spread Lens, Black Housing, UL/CE/CQC</a>	20°	2,121	40.2	423-000011-01	912400130372	120-000185-08	912400130344
<a href="#">100 – 277 VAC, 20° Spread Lens, Gray Housing, UL/CE/CQC</a>	20°	2,121	40.2	423-000011-04	912400133545	120-000185-08	912400130344
<a href="#">100 – 277 VAC, 20° Spread Lens, White Housing, UL/CE/CQC</a>	20°	2,121	40.2	423-000011-00	912400130371	120-000185-08	912400130344
<a href="#">100 – 277 VAC, 40° Spread Lens, Black Housing, UL/CE/CQC</a>	40°	2,047	39.9	423-000011-01	912400130372	120-000185-09	912400130345
<a href="#">100 – 277 VAC, 40° Spread Lens, Gray Housing, UL/CE/CQC</a>	40°	2,047	39.9	423-000011-04	912400133545	120-000185-09	912400130345

## Specification Sheets (cont.)

PDF Download	Beam Angle	Lumens*	Efficacy	Item Number	12 NC	Spread Lens	Spread Lens 12NC
<a href="#">100 – 277 VAC, 40° Spread Lens, White Housing, UL/CE/CQC</a>	40°	2,047	39.9	423-000011-00	912400130371	120-000185-09	912400130345
<a href="#">100 – 277 VAC, 60° Spread Lens, Black Housing, UL/CE/CQC</a>	60°	2,039	39.9	423-000011-01	912400130372	120-000185-10	912400130346
<a href="#">100 – 277 VAC, 60° Spread Lens, Gray Housing, UL/CE/CQC</a>	60°	2,039	39.9	423-000011-04	912400133545	120-000185-10	912400130346
<a href="#">100 – 277 VAC, 60° Spread Lens, White Housing, UL/CE/CQC</a>	60°	2,039	39.9	423-000011-00	912400130371	120-000185-10	912400130346
<a href="#">100 – 277 VAC, 80° Spread Lens, Black Housing, UL/CE/CQC</a>	80°	2,012	39.3	423-000011-01	912400130372	120-000185-11	912400130347
<a href="#">100 – 277 VAC, 80° Spread Lens, Gray Housing, UL/CE/CQC</a>	80°	2,012	39.3	423-000011-04	912400133545	120-000185-11	912400130347
<a href="#">100 – 277 VAC, 80° Spread Lens, White Housing, UL/CE/CQC</a>	80°	2,012	39.3	423-000011-00	912400130371	120-000185-11	912400130347
<a href="#">100 – 277 VAC, 10° x 40° Asymmetric Spread Lens, Black Housing, UL/CE/CQC</a>	10° x 40°	2,201	42.8	423-000011-01	912400130372	120-000185-12	912400130348
<a href="#">100 – 277 VAC, 10° x 40° Asymmetric Spread Lens, Gray Housing, UL/CE/CQC</a>	10° x 40°	2,201	42.8	423-000011-04	912400133545	120-000185-12	912400130348
<a href="#">100 – 277 VAC, 10° x 40° Asymmetric Spread Lens, White Housing, UL/CE/CQC</a>	10° x 40°	2,201	42.8	423-000011-00	912400130371	120-000185-12	912400130348

\* Lumen output measurements comply with IES LM-79-08 testing procedures.

