

3PT20X-NDI-HC20X-NTG Specifications:

PTZOptics PT20X-NDI Specifications:

- Model Number:
 - PT20X-NDI-GY (gray)
 - PT20X-NDI-WH (white)
- Camera & Lens:
 - Video Sensor 1/2.7" CMOS, 2.12 Mega Pixels
 - Frame Rates 1080p/60, 50, 30 & 25, 1080i/60 & 50, 720p/60, 50, 30 & 25
 - Frame Rates (CVBS) 576i/30, 480i/30
 - Focal Length: 20x, F4.42mm-88.5mm, F1.8-F2.8
 - Lens: Zoom 20x
 - Field of View 60.7°
 - Min Lux: 0.5 Lux at F1.8, AGC ON
 - Shutter Speed: 1/30s -1/10000s
 - SNR: >= 55dB
 - Vertical Flip & Mirror: Supported
 - Horizontal Angle of View: 3.36° (tele) to 60.7° (wide)
 - Vertical Angle of View: 1.89° (tele) to 34.1° (wide)
 - Physical Working Environment: Indoor
- Pan & Tilt Movement:
 - Pan Movement: ±170°
 - Tilt Rotation:
 - Up: 90°
 - Down: 30°
 - Presets: 10 via IR (255 via Serial or IP)
- Rear Board:
 - Video Output: NDI|HX, HDMI, 3G-SDI, IP, CVBS
 - Network Interface: RJ45
 - Audio Interface: Line In, 3.5mm (NDI, HDMI & IP Stream)
 - Communication: RS-232, RS485, PELCO-D/P, NDI
 - Baud Rate: 2400/4800/9600 bits
 - Power Supply: JEITA type Power Adapter (DC IN 12V)
 - 3G-SDI Interface: BNC – 75 Ohm, Female
 - USB 2.0 Interface: Future Use
- Electrical Index:
 - Power Supply: 12W (Max)
 - Input Voltage 12V DC (10.8 -13.0V DC) or PoE 802.3af
- Physical:

- Dimension (in.): 5.6 W x 6.5 H x 6.7 D (7.8 H max w/ Tilt)
- Dimensions (mm): 142 W x 164 H x 169 D (198 H max w/ Tilt)
- Box Dimensions: 9" x 9" x 10" (229mm x 254mm x 229mm)
- Camera Weight: 3.10 lbs. (1.41 kg)
- Boxed Weight: 5.4 lbs. (2.45 kg)
- NOTE: This is an FCC Class A Digital device. As such, unintentional electromagnetic radiation may affect the image quality of TV in a home environment.

HuddleCam HC-EPTZ-NDI Specifications:

- Camera & Lens Specifications
 - Field of View: 108°
 - Video CMOS Sensor: 1/2.5" CMOS 8.51M Mega Pixel
 - Focal Length: 2.8mm
 - EPTZ Control Methods: IR Remote, VISCA over IP, HTTP-CGI
 - Compression: MJPEG, YUY2, H.264, H.265
 - Frame Rate: 50Hz: 1 ~ 25, 60Hz: 1 ~ 30
 - Min Lux: 0.05 Lux @ F1.8, AGC ON
 - Zoom: 8x Digital Zoom
- Physical Specifications
 - Connection Interface: RJ-45, USB 2.0 (Future use)
 - Material: Aluminum, Plastic
 - Dimensions (HxWxD): 2.36" x 7.63" x 3.66"
 - Weight: 0.7 lbs
 - Input Voltage: DC 12V / PoE (IEEE 802.3af)
 - Operating Temperature 14°F ~ 104°F
 - Storage Temperature -40°F ~ 140°F

Netgear GSM4212P-100NAS Specifications:

- Primary Port Speed : 1 Gigabit
- Number of Ports : 12 (10x 1G, 2x SFP)
- PoE Ports / Budget : 8 PoE+ (30W/port), 125W Budget
- IGMP Support : Enhanced (NETGEAR IGMP Plus™)
- Jumbo Frame Support : Yes, up to 12kb
- Acoustics : Fanless or 30dB@25°C
- Power Consumption : With PoE: 163.9W/559.555Btu/hr; Without PoE: 17.32W/59.13Btu/hr; Standby without any port connection: 8.53W/29.121Btu/hr
- AVB Support : Yes. Electronic license required, activation key sent via email (AVB4212P-10000S)
- Dimensions (WxDxH) : 440 x 200 x 43.2mm

- Weight : 2.85Kg (6.28lb)

-