BP24V33

External Battery Pack for UPS Systems



Model #: BP24V33

- Extends runtime of Tripp Lite UPS Systems with 24V DC external battery connection
- Provides daisy-chain capability
- Simple installation; stackable
- 2 year warranty

DESCRIPTION

Tripp Lite's BP24V33 external battery pack offers extended battery runtime when used in conjunction with Tripp Lite SmartPro UPS systems with a 24VDC external battery connection. Stackable form factor supports configuration with up to 2 battery packs stacked with the UPS on top. Rugged all metal battery enclosure safely houses UPS batteries and includes heavy gauge cabling with pre-installed DC connectors for simple installation. Additional output connector allows multiple BP24V33 battery packs to be daisy-chained to the UPS for even longer extended run operation.

KEY BUYING POINTS

- Offers extended-run UPS operation when used in conjunction with Tripp Lite UPS systems with a 24V DC external battery connection
- Supports stacking installation of two battery packs with the UPS on top
- Includes input and output connectors to support the connection of multiple battery packs for even longer extended run operation
- Includes heavy gauge cabling with high current DC connectors for simple installation
- 2 year warranty

TYPICAL APPLICATIONS

BP24V33 external battery pack is ideal for lengthening the battery runtime provided by Tripp Lite UPS systems equipped with a 24V DC external battery connection. Additional battery packs may be ordered at time of original UPS purchase or sourced at a later date to extend runtime performance if site power conditions deteriorate and longer battery runtime is desired. COMPATIBLE WITH SMART2200NET, SMART2200XLNET, SMART3000NET, SMART2200RMXL, SMARTINT3000, SMARTINT3000RM and other Tripp Lite UPS systems specifying the use of this pack.

OPTIONS & ACCESSORIES

• Extended warranties: 3 Year WEXT3-BP24V, 5 Year WEXT5-BP24V

PACKAGE INCLUDES

- BP24V33 external battery pack
- Warranty information
- Instruction manual

COMPLETE SPECIFICATIONS

BATTERY

Expandable battery runtime:

Red female DC connector for additional battery packs

DC system voltage: 24 V DC

Typical battery lifespan: 4-6 years typical (North America)

Connects to UPS via: 3 ft. attached cable with red DC connector

PHYSICAL

Shipping weight (lbs): 66

Unit Dimensions (HWD/in): 8 x 11.5 x 13

Material of construction: Putty color steel housing

Form factors supported: Floorstanding tower format. Stackable

CERTIFICATIONS

Certifications: UL, cUL, CE, NOM

WARRANTY

Optional coverage: 3 year, 5 year, next day and on-site warranty coverage available

Product warranty: 2 year product warranty

The policy of Tripp Lite is one of continuous improvement.

Specifications are subject to change without notice.

Therefore, your product may vary slightly from what is currently listed.



Tripp Lite World Headquarters 1111 W. 35th Street Chicago, IL 60609 USA

> Customer Support (773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.