

Network Surge Suppressor

Essential protection for data and communication lines



Model #: DB9

- ▶ Complete serial port (DB9) surge protection
- ▶ Protects against the effects of electrostatic discharge, faulty wiring and lightning
- ▶ Lifetime product warranty
- ▶ Heavy duty grounding lead

DESCRIPTION

Tripp Lite's DB9 offers dataline surge suppression for DB9 serial ports of data terminal and data communications equipment, including PCs, printers, modems and more. User configurable for use with male or female captive DB9 ports. Offers protection on all 9 lines, plus D shell chassis. Convenient DB9 input and output connects directly to the protected port, obtaining a ground outlet from the computer chassis. Surge suppression is handled with balanced arrays of high-speed avalanche diodes that divert excess energies created by electrostatic discharges, faulty wiring or lightning away from network interface connections. Tripp Lite network surge suppressors reduce blown interface cards, garbled transmissions, system lock-ups and hard equipment failure by safely shunting dataline surges to ground. Lifetime warranty.

SUPPRESSION: Reversible DB9 m/f jacks, protects pins 1-9 and chassis, 18V clamping

KEY BUYING POINTS

- DB9 protects 9 pin serial connections for dataline surge suppression of data terminal, data communications equipment and PCs, printers, modems and more
- Reversible for use with male or female captive DB9 ports
- Offers protection on all 9 data lines, plus D shell chassis
- Surge suppression utilizing high speed avalanche diodes divert excess energies on the network to ground
- Lifetime product warranty

OPTIONS & ACCESSORIES

- Ideal for the protection of data terminals, data communications equipment, PCs, printers, modems and more.
- DB9 dataline protector
- Instruction manual and warranty information

PACKAGE INCLUDES

- 1 DB9 Surge Suppressor

COMPLETE SPECIFICATIONS

SYSTEM OVERVIEW

System overview:

Protects RS-232 DB9 serial ports of data terminal and data communication equipment including PCs, printers, modems/faxes, etc. User-configurable ofr either male or femal captive ports.

OUTPUT

Output volt amp capacity (amps): 340 amps

INPUT

Input connection type: DB9

AC SURGE / NOISE SUPPRESSION

Clamping voltage (RMS): 18V

DATALINE SURGE SUPPRESSION

Additional Dataline protection: 1-9 & Chassis

*The policy of Tripp Lite is one of continuous improvement.
Specifications are subject to change without notice.
Therefore, your product may vary slightly from what is currently listed.*



Tripp Lite World Headquarters
1111 W. 35th Street
Chicago, IL 60609 USA

Customer Support
(773) 869-1234

© 2007 Tripp Lite. All Rights Reserved.