

Production Intercom • High Noise Environments • Live Sound Stage • Factory Tours • Military Training

MIC 014

Plug mount microphone



Omnidirectional plug-mount microphone. Can be used with all Williams AV Pocketalkers®. Rigorously tested and approved for quality, reliability and compatibility with Williams AV systems.

MIC 014

Color	Gold
Weight	5 g (0.2 oz)
Plug	3.5 mm Mono
Cord	None
Phantom Powered	No
Pick-Up Pattern	Omni-directional
Transducer Type	Electret Condenser
Mic Diameter	10 mm not including windscreen 19 mm with windscreen
Sensitivity	-42 dB ± 3 dB
Frequency Range	20 Hz - 16 kHz
Output Impedance	2.2 kΩ
Standard Operation Range	2 - 10 V DC
SNR	>58 dB
Replacement Windscreen	WND 002
Optional 12 ft extension cord	WCA 007
Warranty	90 days

Domestic Sales

Williams AV
10300 Valley View Rd
Eden Prairie, MN 55344
Ph: 800-328-6190 / 952-943-2252
FAX: 952-943-2174
Email: info@williamsav.com
Web: www.williamsav.com

International Sales

International Sales Department
Williams AV
10300 Valley View Rd
Eden Prairie, MN 55344 USA
Phone: +1 952 943 2252
Fax: +1 952 943 2174
Email: info@williamsav.com
Web: www.williamsav.com

WILLIAMS AV
info@williamsav.com / www.williamsav.com
800-843-3544 / INTL: +1-952-943-2252