

floor rack with removable sides, rear access cover, tempered glass door
35U x 24"D x 22"W



features.

- **Panel Space:** 35U or 61.25" [1556]
- **Overall Height:** 65.43" [1662]
- **Overall Depth:** 24.00" [610]
- **Usable Depth:** 22.00" [559]
- **Overall Width:** 22.31" [567]
- **Description:** Elegant floor rack for 19" equipment is designed for an executive boardroom, home theater or office. Includes tempered glass front door and rear access cover.
- **Construction:** Welded steel frame with removable side panels, rear access cover, and tempered glass door. 16-gauge certified U.S. steel with top and base reinforced at loadbearing junctions. Charcoal Grey textured finish. Beveled edge corners.
- **Front:** Includes smoked grey tempered glass door with inset handle and key lock. Mounts left or right.
- **Rear:** Removable rear access cover with key lock opens from the top. Rear cover is keyed the same as side panels.
- **Sides:** Removable side panels with key locks are keyed the same as rear door.
- **Base:** Large 12" x 12" opening in center of base, plus two holes with grommets for cable access. Includes 10-32 threaded grounding stud and four leg levelers.
- **Top:** Steel top features two vents and a center hole with grommet for cable access.
- **Cable Management:** Hole with grommet in top and base.
- **Rack Rails–35U (fully adjustable):** Two pairs of 11-gauge steel, 10-32 threaded rails with rack unit increments printed on E.I.A. spacing.
- **Hardware:** Black pilot point screws with captive washers for quick installation.
- **Compliance:** EIA/TIA compliant. RoHS compliant.
- **Load Capacity:** 980 lbs. [444 kg]

a&e specifications.

The EIA/TIA compliant 19" equipment rack shall be Lowell #LDR-3524 with overall dimensions of 22.31"W x 24.00"D x 65.43"H, providing 35U panel space. Construction shall be welded 16-gauge steel frame with top and base reinforced at loadbearing junctions. It shall have a Charcoal Grey textured finish. The rack shall include a smoked grey tempered glass front door with key lock, recessed rear access cover with key lock, removable side panels with key locks, two pairs of 11-gauge steel adjustable rails with mounting holes tapped 10-32 and rack unit increments printed on EIA spacing. The steel top shall have two vents and a hole with grommet for cable management. The base shall feature a center opening, two holes with grommets, and a grounding stud. The rack shall include four leg levelers.

LDR series summary

Model No.	Rack Units	Overall Depth	Usable Depth	Overall Height	Usable Height	Overall Width	Bottom Opening Depth	Bottom Opening Width	Adjustable Rails	Load Capacity lbs.
LDR-1824	18 U	24.00 [610]	22.00 [559]	35.67 [906]	31.50 [800]	22.31 [567]	12.00 [305]	12.00 [305]	2 pr	500
LDR-2724	27 U	24.00 [610]	22.00 [559]	51.42 [1306]	47.25 [1200]	22.31 [567]	12.00 [305]	12.00 [305]	2 pr	750
▶ LDR-3524	35 U	24.00 [610]	22.00 [559]	65.43 [1662]	61.25 [1556]	22.31 [567]	12.00 [305]	12.00 [305]	2 pr	980
LDR-4224	42 U	24.00 [610]	22.00 [559]	77.68 [1973]	73.50 [1867]	22.31 [567]	12.00 [305]	12.00 [305]	2 pr	1200

Rack dimensions (rounded) – inches and [mm]
1U = 1.75"



