



## ENCORE LP5IP

Versatile, heavy duty IP65 Rated Par with seven (5) 20W Quad LEDs (4-IN-1: Red, Green, Blue & Lime) + tunable white color temperature control from 2700K - 7000K.

The ADJ Encore LP5IP is a versatile IP65 outdoor rated Par with 5 x 20-Watt (4-IN-1: Red, Green, Blue & Lime) Quad LEDs. With a 10° beam angle, users may produce wide washes with smooth color mixing from 64 built-in color macros utilizing red, green, blue and lime LEDs. Not only is this LED Par great for lighting indoor stages and venues, but with its IP65 rating, it's a great solution for temporary outdoor lighting of stages or events. The IP65 rating helps protect the fixture from rain, snow and dust.

The fixture's Quad LED engine offers flicker free operation for TV and film and linear white color temperature control from 2700K to 7000K.

The Encore LP5IP professional features include: 6 DMX modes, 5 operational modes, 6 selectable dimming modes, 4 selectable dimming curves, and a 4-Button DMX menu with digital display. The unit is equipped with outdoor Locking Power connectors and IP rated 5-pin DMX rubber covers and connectors. IP rated power linking and DMX cables are available, but standard 5-pin DMX cables may also be used for indoor applications.

The Encore LP5IP includes a removable 25-degree frost filter. There are several additional frost filter options (sold separately) that customize the beam angle.

[www.ADJ.com/encore-lp5ip](http://www.ADJ.com/encore-lp5ip)



## SOURCE:

- Light Source: 5 x 20-Watt Quad RGBL LEDs  
(4-IN-1: Red, Green, Blue & Lime)

## PHOTMETRIC DATA:

- Beam angle: 10-degree
- CRI: 84
- CRI R9: 76.6
- Lumens: 700+

## EFFECTS:

- Linear Color Temperature Control (2700K to 7000K)
- Preset Color Temperatures (2700K, 3200K, 4000K, 5600K and 6500K)
- 16-Bit Fine Color Control (Red, Green, Blue & Lime)
- 64 built-in Color Macros

## CONTROL / CONNECTIONS:

- 4-button, DMX digital display on rear panel
- 5 Operational modes: Static Color Mode, RGBL Dimmer Mode, Program Mode, Sound Active Mode and DMX Controlled
- Supports RDM (Remote Device Management)
- With Wired Digital Communication Network
- 6 selectable Dimming Modes (Standard, Stage, TV, Architectural, Theatre & Stage 2)
- 4 selectable Dim Curves (Linear, Square Inv. Squa, S-Curve)
- Adjustable Refresh Rate (14 presets from 900 – 25,000Hz)
- Flicker Free operation (No flickering on camera)
- LED pulse and strobe effect
- Electronic Dimming: 0 - 100%
- 6 DMX Modes: 4, 7, 8, 10, 13, & 16-channel
- Quiet fan mode

## CONSTRUCTION:

- IP65 Rated: Ingress Protection against liquid, snow, dust and sand
- All metal construction
- IP Rated rubber covers protect In/Out Locking Power connectors and IP rated 5-pin sockets
- Locking, outdoor IN/Out Power connectors
- Data linkable via 5-pin XLR DMX connections
- Scissor Yoke & safety eye

## APPROVALS / RATINGS:

- cETLus Pending • IP65



## ELECTRICAL / THERMAL:

- Multi-voltage operation: AC 100-240V, 47/63Hz
- Daisy chain: 21 units max (110V) / 44 units max (240v)
- Max power: 32W

## DIMENSIONS / WEIGHT:

- Dimensions (LxWxH): Dimensions (LxWxH): 5.92" x 8.23" x 10.06" / 150.48mm x 209.00mm x 255.40mm
- Weight: 5.3 lbs / 2.4 kgs

## INCLUDED ACCESSORIES:

- (1) Dual Side Frost Filter
- (1) Power Cord

## ACCESSORIES:

**ELP5L100:** 100-degree frost filter for the Encore LP5IP

**ELP5L60:** 60-degree frost filter for the Encore LP5IP

**ELP5L30X60:** 30x60-degree frost filter for the Encore LP5IP

**ELP5L1X40:** 1x40-degree frost filter for the Encore LP5IP

**ELP5L20:** 20-degree frost filter for the Encore LP5IP

Preliminary information - specifications subject to change.

