



LED Shadow 2 ILS

Amazing black light effects step out of the shadows with LED Shadow 2 ILS, a versatile black light with brilliant eye candy effects and compatibility with the cutting edge Integrated Lighting System (ILS) that makes creating coordinated light shows across different fixture types easy. D-Fi USB compatibility is also on board for wireless Master/Slave, or DMX control. LED Shadow 2 ILS lets you generate complex looks easily with built-in, eye-catching auto programs with sectional control and access built-in automated programs via IRC6 remote, Master/Slave, or DMX. LED Shadow 2 ILS is ideal for sound-sensitive environments due to the radiant cooling design. Achieve smooth LED fading with built-in dimming curves.



Highlights

- Versatile black light with brilliant eye candy effects
- ILS compatibility for use in the ILS ecosystem
- D-Fi USB compatibility for wireless Master/Slave, or DMX control
- Generate complex looks easily with built-in, eye-catching auto programs with sectional control
- Access built-in automated programs via IRC6 remote, Master/Slave, or DMX
- Achieve smooth LED fading with built-in dimming curves
- Ideal for sound-sensitive environments due to the radiant cooling design
- Save time running extension cords by power linking multiple units

Specifications

- DMX Channels: 4 or 8
- DMX Connectors: 3-pin XLR
- Light Source: 18 LEDs (UV) 3 W, (0.6 A), 50,000 hours life expectancy
- Strobe Rate: 0 to 20 Hz
- Coverage Angle: 32°
- Power Linking: 11 units @ 120 V; 20 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current:
 - 49 W, 0.7 A @ 120 V, 60 Hz
 - 49 W, 0.4 A @ 230 V, 50 Hz
- Weight: 6 lb (2.8 kg)
- Size: 8.2 x 14 x 2.2 in (208 x 355 x 55 mm)
- Approvals: CE, RoHS, UKCA
- Optional Controllers: IRC-6
- Wavelength: 405 nm

What's Included

- Power cord
- Hanging Bracket with Mounting Hardware
- Warranty Card