





L70 Series desktop cabinets Model L70-24 shown with optional front door Model L151-24 and optional rear door Model L7-1922



L70 Series Desk Cabinets

Cabinets Include:

- Fixed Front Mounting Rails: One pair tapped 10-32
- Fixed Rear Mounting Rails: One pair punched .281 •
- Recessed Handle Grips
- Protective Rubber Feet •
- Side Ventilation slots
- Wrinkle Powder Epoxy Finish: Choose Black (standard) or ٠ Network Grey (suffix -G).

Ordering Options (suffix Model number)

• -G Network Grey Finish. Neutral computer/putty color.

Accessories (optional - order separately)

- Recessed Front Door (Lock is keyed different than rear door)
- Recessed Rear Door: Door is 2" shorter than opening to facilitate wire access (Lock is keyed different than front door).

Description

Lowell's UL Listed (Standard 1678) desk cabinet Series L70 is designed specifically to provide ready access and security for 19"W audio, video, control and other equipment used in desktop applications. Choose from five panel space sizes equipped with 1/2" protective rubber feet to prevent scratching of desk surfaces, side ventilation slots for heat dissipation, and recessed finger pockets for easy maneuverability.

The cabinet assembly is welded 16-gauge certified US steel with 11-gauge fixed front mounting rails tapped 10-32 and punched rear rails on .281 universal EIA spacing. Front rails are recessed 1.812" from the frame providing 1.687" equipment clearance - even when an optional recessed front door is installed. Total useable mounting depth is 15.937". Finish is Lowell's durable wrinkle powder epoxy in black or Network Grey (suffix -G).

Options include a locking solid front door (recessed) with spring loaded hinges for left or right orientation and a solid rear door (recessed) that is 2" shorter than the opening to facilitate cord and cable entry. Both doors are locking and are keyed differently for security.

SPECIFICATIONS FOR LOWELL DESK CABINET SERIES L70											
	Cabinet	Racking	Overall	0.A.	O.A. Depth	Fixed	Rear	Front	Weight	Front Door*	Rear Door*
	Model*	Height A	Height B (incl. feet)	Width	(15.937" useable)	Rails Installed	Opening	Opening		Recessed-solid (Order separately)	Recessed-solid (Order separately)
ups	L70-12	12.375" (7RU)	14.875"	21.125"	18.5"	1pr	Open	Open	34 lbs.	L151-12	**L7-1910
ups	L70-17	17.625" (10RU)	20.125"	21.125"	18.5"	1pr	Open	Open	36 lbs.	L151-17	**L7-1915
ups	L70-21	21.125" (12RU)	23.625"	21.125"	18.5"	1pr	Open	Open	39 lbs.	L151-21	**L7-1919
ups	L70-24	24.625" (14RU)	27.125"	21.125"	18.5"	1pr	Open	Open	43 lbs.	L151-24	**L7-1922
	L70-31	31.625" (18RU)	34.125"	21.125"	18.5"	1pr	Open	Open	50 lbs.	L151-31	**L7-1929

*Standard color for cabinets and doors is black wrinkle powder epoxy. To order Network Grey on cabinets and doors, suffix each Model with -G.

**L7 Series locking rear doors are 2" shorter than the opening to facilitate wire access.

UDS Noted Models (all but L70-31) are suitable for UPS shipment.



フ

A C

ス

C

A & E Specifications

Cabinet for desktop use shall be Lowell Model

_____(L70-12, L70-17, L70-21, L70-24, L70-31). Cabinet shall measure 21.125"W x 18.5"D (15.937" usable depth) x ____"H and shall be UL Listed under Standard 1678. Welded

assembly shall be 16-gauge certified US steel with 11-gauge fixed front mounting rails tapped 10-32 and punched rear rails on .281 universal EIA spacing. Desktop cabinet shall include side ventilation slots, recessed finger pockets, and protective rubber feet. Finish shall be Lowell's powder epoxy in ____(black, Network Grey). **Options:** Desktop cabinet shall include an <u>optional locking</u> <u>rear door</u> (L7-1910, L7-1915, L7-1919, L7-1922, L7-1929) that is 2" shorter than the cabinet panel space to provide security and ample space for cord and cable entry. Cabinet shall include an <u>optional locking front door</u>

_____(L151-12, L151-17, L151-21, L151-24, L151-31) that mounts flush using spring loaded hinges for right or left swing. Doors shall be finished in _____ (Black, Network Grey) powder epoxy paint.



L70 Series Dimensions