

INNOVOX AUDIO LLC

Product Data Sheet for: LA-1400 line array loudspeaker

Description: The LA-1400 loudspeaker is an ultra-compact 2-way line array system featuring a ribbon tweeter and four 4" woofers. Very flat response, controlled vertical dispersion, superb vocal clarity, and an enclosure well under 4" thick make the LA-1400 an excellent choice for performing-arts centers, smaller churches and similar medium-throw applications requiring smooth, articulate response and controlled dispersion.

Applications: Small churches
Choir lofts
Performing-arts centers
Schools

Dimensions: 25.62" x 5.62" x 3.38"

System type: 2-way sealed box with four (4) 4" woofers and one (1) ribbon tweeter

Construction: Cold-rolled steel chassis with MDF endcaps

Mounting: Four (4) 1/4-20 threaded holes in back for Omni Mount series 30 bracket
Holes in endcaps accept optional split-U bracket.

Impedance: 8 ohms (70-volt version available)

Sensitivity: 93 dB @ 1watt / 1 meter

Max power: 150 watts long-term program

Max output: 114 dB long term, averaged from 300 – 3,000 Hz

Range: 130 – 20,000 Hz +/- 3 dB relative to nominal sensitivity

Dispersion: 140H x 40V

Standard finish: Black or White fabric / matching painted endcaps

INNOVOX AUDIO LLC

Product illustration / photo of: LA-1400 line array loudspeaker

