

1T-C2-400 PC/HD Scaler is based on TV One's exclusive CORIO2™ technology and provides bi-directional, high quality conversion between Computer and HDTV signals in a compact package. Both input and output support any computer resolution up to 2048x2048 at any vertical refresh rate and all HDTV resolutions up to 1080p. Cross conversion within formats is also supported. The wide variety of computer signal formats available support PC, Mac and Workstation formats as well as analog HDTV display devices.

All the functions can be controlled via the front panel Push Buttons, an Infrared Control Remote Unit or via an RS-232 connection. A Windows Control Panel is provided and most third party control systems interface directly with the entire C2 range of products. An On-Screen Display is available to assist in setup. Variable Zoom to 10X allows you to enlarge any part of the video image to fill the entire computer screen. The full bandwidth chroma sampling insures faithfully reproduced, high resolution colors.

CORIO 2 Technology



This symbol on a product indicates that it is powered by CORIO2™ technology, the most flexible video processing engine now available.

Unlike most manufacturers, who use third party chipsets to provide video conversion, TV One has developed its own proprietary technology known as CORIO2™. This frees TV One products from the constraints imposed by third parties and results in an unsurpassed degree of



Key Features of the 1T-C2-400

- Automatic incoming resolution detection
- RGB/YPbPr Input and Output
- PC Resolution up to 2048 x 2048, In and Out
- HDTV up to 1080P, In and Out
- Converts PC to HDTV or HDTV to PC
- Converts PC to PC or HDTV to HDTV
- RS-232 Interface and Windows Control Panel
- IR Remote Control
- Variable Image Zoom to 10X
- Optional Single/Dual Rackmount Kit

flexibility. Products based on third party chipsets have a feature set frozen at the introduction of the product. Since the CORIO2™ video processing engine is entirely firmware based, it can be upgraded at any time by downloading the latest firmware version from the support website and flash upgrading the unit in the field. This enables new features to be added to units many years after the initial purchase. This "obsolescence insurance" means that a CORIO2™ based product can always be upgraded to the latest

Specifications

Input/Output

Format - Analog	RGBHV, RGBS, RGsB, YPbPr
Connectors	1x HD-15 Female
R-G-B Level	0.7 Vp-p
PC Resolutions	Any up to 2048x2048
HDTV Resolutions	Any up to 1080p
Vertical Refresh Rate	Any to 250Hz

General

Size and Position	Automatic via AutoSet or Manual
Image Freeze	One Video Frame
Settings Memory	Non-Volatile
Zoom Range	Variable to 10X Zoom
Conversion Technology	Proprietary – CORIO2™
Firmware Memory	Flash, Upgradeable via RS-232
Video Adjustments	R-G-B Levels

Control Methods

Local	via Front Panel Buttons & OSD
RS-232 Interface	via D9 Female Connector
Infrared Remote	via IRC-5 Remote Unit

Warranty

Limited Warranty	2 Years Parts and Labor
------------------	-------------------------

Regulatory Compliance

Main Units	FCC, CE, RoHS
Power Supplies	UL, CE, CSA, RoHS

Mechanical

Size (H-W-D)	1.2"x7.9"x3.5" (30x200x89mm)
Weight (Net)	1.3 lbs (580g)

Environmental

Operating Temperature	+4° to +45° C (+40° to +113° F)
Operating Humidity	10% to 85%, Non-condensing
Storage Temperature	0° to +60° C (+32° to +140° F)
Storage Humidity	10% to 85%, Non-condensing

Power Requirement

External Power Supply	12VDC@1A
-----------------------	----------

Accessories Included

1x VGA Cable	6' (2m) HD15 Male to Male
1x IR Remote	IRC-5

Product Item Number

1T-C2-400	PC/HD Scaler
-----------	--------------

Optional Accessories

RM-230	Single/Dual Rackmount Kit
--------	---------------------------

Panel Drawings

