





The VP-419xl is a high performance digital scaler for composite, s-Video and component (480i) video signals. It will scale a video input to a selectable graphics or HDTV output resolution.

DESCRIPTION

HDTV Output Resolutions - 480p, 576p, 720p, and 1080i in component format on the HD-15 output connector. Multi-Standard Video Signal Compatibility - NTSC 3.58 & PAL-B/G/I/ID Built-in Proc-Amp - Color, hue (NTSC only), sharpness, contrast, and brightness 3-D Comb Filter - On/Off

3.2 Pull Down Video Processing - Auto detection.

Multiple Aspect Ratio Selections - 4x3 or 16x9

Digital Noise Reduction - On/Off

Computer Graphics/HDTV (15-Pin HD) Pass-thru

Flexible Control Options - Front Panel buttons, IR Remote (with on-screen menus)

Desktop Size - Compact size, 1RU high. Two units can be rack mounted side by side in a 1RU rack space with the optional RK-80N adapter.

SPECIFICATIONS INPUTS:

OUTPUT: 1 RGB/YPbPr on an HD15F connector

OUTPUT RESOLUTIONS: VGA (640x480), SVGA (800x600), XGA (1024x768), SXGA (1280x1024), HDTV: 480p, 576p, 720p, 1080i CONTROLS: Front panel buttons and infra red remote for menu driven OSD control

ADDITIONAL CONTROLS: Contrast, brightness, color, tint and sharpness; Resolution, output image scaling, output mode, 3D comb filter function and aspect ratio

POWER SOURCE: 12V DC, 350mA

DIMENSIONS: 215mmx163mmx43.6mm (8.46"x6.4"x1.7")W, D, H

WEIGHT: 0.25kg (0.55lb.) approx. ACCESSORIES: Power supply, IR remote control OPTIONS: RK-80N 19" rack adapters.

© www.kramerelectronics.com 2007

1 VGA/SVGA/XGA/SXGA on an HD15F connector; 1 composite video on an RCA connector; 1 component video (Y, Cb, Cr) on RCA connectors; 1 s-Video on a 4p