



DESCRIPTION

The GAD GT-1071™ is a two-way bass reflex loudspeaker system featuring flat frequency response, low distortion, and wide dynamic range. Designed for permanent and semi-permanent applications.

The GT-1071™ is available with several installation choices including 3/8" - 16 threaded mounting points, a U-Bracket or a swivel Multimount™.



APPLICATION

The GT-1071™ is designed for near-field applications where a smooth, dynamic range is needed. The GT-1071™ is an ideal choice for either analog or digital reproductions where a clear, clean response is a must. The GT-1071™ boasts wide-range dispersion for portable A/V events of even for a side-fill or delay monitoring applications.

SPECIFICATIONS DATA

Frequency Response (1 watt @ 1M)	+ 3db 70 Hz 17 kHz	
Sensitivity (1 watt @ 1M)	(2.83V) 99 db SPL	
Power Handling	AES standard 250 watts	
Nominal Impedance	8 ohm	
Dispersion	Horizontal 60°	
	Vertical 60°	
Cabinet Type	Trapezoidal 15°	
Finish	Black Spatter	
Connectors	2 x Neutrik® NL4 Speakon	
Grille	Powder-Coated, Perforated Steel	
Crossover Frequency	2.8 Hz with 18 db per octave slope	
Components	LF: 10 cone MF: n/a HF: compression driver	

Dimensions	Inches		Millimeters	
	Height	18.75		477
Width	12.5		318	
Depth	12.75		325	
Weight	Pounds		Kilograms	
	Net Weight	29		13.2

grundorf
corp.™

712-322-3900
FAX 712-322-3407

Visit us online at www.grundaudio.com
Email: sales@grundaudio.com

721 Ninth Avenue - Council Bluffs, IA 51501