


1T-VGA-CAT. 1T-VGA-CAT-XL. 1T-VGAx-CAT-TXL. 1T-VGA-CAT-RXL



1T-VGA-CAT-XL has the same features, resolution. encode and decode capabilities of the 1T-VGA-CAT but doubles the range to 1000 feet (300m). VGA loop-thru is provided on the 1T-VGA-CAT-XL Transmitter.

1T-VGA4-CAT-TXL and 1T-VGA8-CAT-TXL encode a VGA signal of up to 1280x1024 resolution and feed 4 or 8 CAT 5 cables respectively over distances of up to 1000 feet (300m). VGA loop-thru is provided with these units.

1T-VGA-CAT-RXL decodes signals received via CAT 5 cables from the 1T-VGA4-CAT-TXL or 1T-VGA8-CAT-TXL transmitter. A dedicated CAT 5 cable plus a dedicated 1T-VGA-CAT-RXL receive unit is required for each remotely located VGA display device. Equalization and gain controls are provided for each receiver.

# **Specifications**

Video Inputs	
1T-VGA-CAT (Transmitter)	1xHD-15 VGA Connector
1T-VGA-CAT-XL (Transmitter)	2xHD-15 (loop thru Connectors)
1T-VGA4-CAT-TXL	2xHD-15 (loop thru Connectors)
1T-VGA8-CAT-TXL	2xHD-15 (loop thru Connectors)
Video Outputs	
1T-VGA-CAT (Receiver)	1xHD-15 VGA Connector
1T-VGA-CAT-XL (Receiver)	1xHD-15 VGA Connector
1T-VGA-CAT-RXL	1xHD-15 VGA Connector
CAT 5 Connectors	
1T-VGA-CAT	2xRJ-45 (1Transmit + 1Receive)
1T-VGA-CAT-XL	2xRJ-45 (1Transmit + 1Receive)
1T-VGA4-CAT-TXL	4xRJ-45 (4 Transmit)
1T-VGA8-CAT-TXL	8xRJ-45 (8Transmit)
1T-VGA-CAT-RXL	1xRJ-45 (1 Receive)
Resolution	
All units	Up to 1280x1024
Signal Adjustments	
Equalization and Gain	All Receivers
Range	
1T-VGA-CAT	590 Ft (180m)
1T-VGA-CAT-XL	1000 Ft (300m)
1T-VGA4-CAT-TXL	1000 Ft (300m)
1T-VGA8-CAT-TXL	1000 Ft (300m)
1T-VGA-CAT-RXL	1000 Ft (300m)
Cable Requirements	·
CAT 5/5E or CAT 6	Network Grade, Premium Cables
Enclosure Type	
Metal w/ scuff resistant feet	All Products







1T-VGA-CAT Transmitter & Receiver





1T-VGA4-CAT-TXL

1T-VGA8-CAT-TXL







Rear: 1T-VGA4, 8-CAT-TXL

1T-VGA-CAT-RXL

### **Key Features of the CAT 5 VGA Extenders**

- Remotely view PC displays via CAT 5 Cable
- Resolutions to 1280x1024
- Ranges up to 1000 Feet
- Up to 8 monitors fed from single transmitter
- Gain and equalization adjustments at each receiver

### Mechanical Size (H-W-D)

0120 (11 11 0)	
1T-VGA-CAT & XL (R&T)	0.86"x1.3"x3.6" (22x34x92mm)
1T-VGA4-CAT-TXL	1.16"x5.1"x3.3" (29.5x130x83.5mm)
1T-VGA8-CAT-TXL	1.16"x7.9"x3.3" (29.5x200x83.5mm)

11 10/10 0/11 1/12	TITO XI TO XOLO (ECTORECTIONI)
1T-VGA-CAT-RXL	0.86"x1.3"x3.6" (22x34x92mm)
Weight (Net)	
1T-VGA-CAT & XL (R&T)	T=0.27lbs (135g), R=0.31lbs (140g)
1T-VGA4-CAT-TXI	0.5lbs (247g)

## 1T-VGA8-CAT-TXL 1T-VGA-CAT-RXL

### 0.76lbs (345g) 0.31lbs (140g) Warranty

#### Limited Warranty 2 Years Parts and Labor Environmental

Operating Temperature 0° to +48° C (+32° to +120° F) Operating Humidity 10% to 85%, Non-condensing Storage Temperature -10° to +70° C (+14° to +158° F) Storage Humidity 10% to 85%, Non-condensing **Power Requirement** 

#### **External Power Supply** +12 VDC@600ma, Locking DC **Regulatory Approvals**

Encoder/Decoder Unit FCC, CE **Power Supply** UL, CE, CSA

# **Accessories Included**

(Per device), US, UK or Euro Type 1x Power Adapter 1x VGA Cable 4 Ft (1.2m) HD-15 to HD-15 CAT 5 VGA Extender Series 1x User Manual


### **Product Item Number** 1T-VGA-CAT


CAT5 VGA Extender, Std. Range\* 1T-VGA-CAT-XL CAT5 VGA Extender, Ext'd. Range 1T-VGA4-CAT-TXL 4 output CAT5 VGA Xmit., Ext Range 1T-VGA8-CAT-TXL 8 output CAT5 VGA Xmit., Ext Range 1T-VGA-CAT-RXL CAT5 VGA Dedicated Receiver\*

\* No VGA Cable provided for this product - Cable not needed.

1T-VGA-CAT, 1T-VGA-CAT-XL, 1T-VGAx-CAT-TXL, 1T-VGA-CAT-RXL

# **Sample Systems**







1T-VGA-CAT, 1T-VGA-CAT-XL, 1T-VGAx-CAT-TXL, 1T-VGA-CAT-RXL

## **Panel Drawings**














## **1T-VGA-CAT Transmit and Receive**













# 1T-VGA-CAT-XL Transmit and Receive



1T-VGA4-CAT-TXL



1T-VGA-CAT, 1T-VGA-CAT-XL, 1T-VGAx-CAT-TXL, 1T-VGA-CAT-RXL



1T-VGA8-CAT-TXL



1T-VGA-CAT-RXL