

speco technologies®

## Triplex Digital Video Recorder Family with Network/DDNS Video Server



**DVR-4TL/160\* • DVR-8TL/160\* • DVR-16TL/160\***

4 Channel Triplex MPEG-4 DVR • 8 Channel Triplex MPEG-4 DVR • 16 Channel Triplex MPEG-4 DVR

### Features

**EZ Record:** set the number of days you want to record and the DVR takes care of the rest  
**EZ Copy:** auto copy what you are playing onto a USB flash drive  
**EZ Set-Up:** for quick Installation

- Free DDNS server for use with dynamic IP addresses
- MPEG-4 high quality compression, 5~10 times smaller than MJPEG
- Triplex operation enabling simultaneous live view or playback while continuing to record & network transfer
- Remote monitoring, recording, playback, change system settings and dome camera control via Ethernet and/or Internet
- Recording Rate: Up to 60pps
- 1 Channel in/out for audio recording
- USB 2.0 port for video clip exporting, supports USB ThumbDrive®
- Easy software upgrade via USB ThumbDrive®
- Multiple built-in dome camera protocol (through RS485): including Pelco D, Pelco P, AD422, Fastrax, DynaColor, JVC, Panasonic
- Automatic camera detection (Plug & Play)
- Digital Zoom 2 x 2 in live mode, playback
- Covert camera operation provides enhanced security and administrator control
- Dynamically programmable recording priority, motion detection, alarms, and scheduling, continuous
- Programmable call-monitor switching sequence
- Multiple language on-screen menus
- Password to secure installation authorization
- Network software supports static IP, DHCP, PPPoE and DDNS
- Network hardware supports 10/100M bps
- Dimensions: 2" (H) X 17 1/4" (W) X 16 1/8" (D)
- Weight: 18 lbs. with 1 HDD (HDD weighs 1 lb.)
- Power Consumption: Start up @ 80 Watts, Running @ 50 Watts
- Heat Dissipation: 2.85 BTU/Minute
- HDD size: 160GB, 320GB, 750GB
- Operating temperature: 32° F to 104° F
- Web-based remote software
- Remote control, rack ears & I/O connect all included

\* Standard DVR comes with a 160GB HDD. Other configurations available up to 1.5TB internal

Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: [www.specotech.com](http://www.specotech.com)  
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880

MPEG-4 TRIPLEX DVR

## Specifications: 4, 8 or 16 Channel MPEG-4 Triplex Digital Video Recorders with 160GB HDD

|                     | MODEL NAME                |              | DVR-4TL/160  | DVR-8TL/160                   | DVR-16TL/160                   |
|---------------------|---------------------------|--------------|--|-------------------------------|--------------------------------|
| Video               | Operation System          |              | Embedded ( Linux )   |                               |                                |
|                     | Video Standard            |              | NTSC/PAL   |                               |                                |
|                     | Video Operation           |              | Triplex+ ( Live, Record, Playback , Remote, and Internet access )  |                               |                                |
|                     | Resolution – Live Video   |              | NTSC: 720 x 240 pixels   |                               |                                |
|                     | Input                     |              | BNC x 4,<br>1.0Vp-p/75<br>ohm                                      | BNC x 8,<br>1.0Vp-p/75<br>ohm | BNC x 16,<br>1.0Vp-p/75<br>ohm |
|                     | Outputs                   | Main Monitor | BNC x 1, 1.0Vp-p/75 ohm  |                               |                                |
|                     |                           | Call Monitor | BNC x 1, 1.0Vp-p/75 ohm  |                               |                                |
|                     |                           |              |  |                               |                                |
|                     | Live Picture Refresh Rate |              | NTSC: 60 PPS   |                               |                                |
|                     | Digital Zoom              |              | 2 x 2 (Live & Playback)  |                               |                                |
| Camera Installation |                           | Plug & Play  |  |                               |                                |
| Audio               | Input                     |              | RCA x 1, Line-In   |                               |                                |
|                     | Output                    |              | RCA x 1, Line-Out  |                               |                                |
|                     | Recording Mode            |              | Always Real Time Record, Synchronized w/ Video                     |                               |                                |
|                     | Compression Method        |              | ADPCM, G.726   |                               |                                |
|                     | File Size                 |              | 8KB/Sec  |                               |                                |
|                     | Operation                 |              | Remote + VCR mode  |                               |                                |
|                     | Playback                  |              | Only for Video Original Speed                                      |                               |                                |
| Recording           | Compression Method        |              | MPEG-4 Advanced Simple Profile                                     |                               |                                |
|                     | Recording Mode            |              | Continuous, Schedule, Alarm, Motion Detection                      |                               |                                |
|                     | Resolution & Rate         | NTSC         | 720x480: 30 pps<br>720x240: 60 pps                                 |                               |                                |
|                     |                           | PAL          | 720x576: 25 pps<br>720x288: 50 pps                                 |                               |                                |
| Playback            | Recording Quality         |              | 5 levels presets, adjustable                                       |                               |                                |
|                     | Image Size                |              | 2K to 20K Byte/picture   |                               |                                |
|                     | Storage Mode              |              | Linear/Circular  |                               |                                |
|                     | Playback                  |              | Play, Stop, Pause, Rewind, Forward, Search                         |                               |                                |
|                     | Playback Speed Adjustment |              | Yes 1X, 2X...32X   |                               |                                |
|                     | Retrieve                  |              | Date/Time, Event   |                               |                                |
| Storage             | Built-in Storage          |              | X1 ATA 133 / UDMA 133 IDE, HDD                                     |                               |                                |
|                     | Export                    |              | USB 2.0 port (single port on front), supports ThumbDrive®          |                               |                                |
| Alarm               | Alarm Input               |              | X4, D-sub 15-pin   | X8, D-sub 25-pin              | X16, D-sub 25-pin              |
|                     | Alarm Detection           |              | N.C./N.O., Programmable  |                               |                                |
|                     | Auditory Alert            |              | Built-in Buzzer  |                               |                                |
|                     | Motion Detection          |              | 16 x 12(NTSC), Grid Array,<br>Sensitivity, Trig Level Adjustable   |                               |                                |
|                     | Video Loss Detection      |              | Programmable   |                               |                                |
|                     | Alarm Relay Output        |              | X1, 1.0A/24V (Programmable)  |                               |                                |
| Communication       | Network Connectivity      |              | Ethernet RJ-45 connector, 10/100Mbps, supports DHCP/PPPoE/DDNS     |                               |                                |
|                     | Remote Control Software   |              | Internet Explorer  |                               |                                |
|                     | Access Control            |              | 2 Level Password   |                               |                                |
|                     | Remote Operation          |              | Monitoring, Playback, Recording, System Setup, Dome Camera Control |                               |                                |
|                     | RS485                     |              | D-sub 15-pin   | D-sub 25-pin                  | D-sub 25-pin                   |
|                     | Dome Control Protocol     |              | DynaColor, Pelco P, Pelco D, AD422, Fastrax, JVC, Panasonic        |                               |                                |