

TURN MOST ANY POWERED SPEAKER INTO A UHF WIRELESS PA SYSTEM

Galaxy Trek GTU Wireless Portable Microphone system features 160-foot range and UHF frequency wireless transmitter options with choice of handheld, headset, or lavalier mics. Additionally, the user-friendly compact dual mic receiver enables use of any two of the microphone transmitter options simultaneously.

The Galaxy Trek GTU incorporates *Auto Match Pairing* to connect transmitters to an open channel. Simply turn on the Receiver and 1 or 2 Transmitters to seamlessly sync. Plug the Galaxy Trek Receiver into the 1/4" input of active speakers, mixers, cameras, and more for instant wireless connectivity. The Galaxy Trek GTU system also includes a 1/4" to 1/8" adapter for smart devices and cameras.

Dual Mic systems available in a variety of configurations, from handheld, headset, or lavalier microphones. Mix and match your system.

Combine the Trek GTU with a powered loudspeaker to create a versatile wireless PA system for classroom instruction, sports coaches, corporate and trade-show presenters, aerobics instructors, auctioneers, religious ceremonies, weddings and more.

AUTO MATCH PAIRING

Simply turn on the Receiver and 1 or 2 Transmitters and they will automatically sync. Plug the Receiver into a powered speaker and you're ready to be heard.

- Dual Channel Wireless Receiver
- UHF Wireless Transmission
- Compact Light-Weight Design
- Full Range Microphone
- Easy Set Up
- 160 ft Operating Range*
- 6 Hours Battery Life



DUAL CHANNEL RECEIVER

**Allows Two Mics
To Be Used
SIMULTANEOUSLY**



Specifications:

GTU System

Pairing: Auto-Match (automatically syncs)
Audio Frequency Response: 80Hz-15KHZ
Frequency Stability: +- 0.005%
S/N Ratio: >60dB
THD: 0.5%(1khz)
Sensitivity: -70dbm
Operating Range: 160ft (50 meters)*
RF power: 20mW
Bandwidth: 60MHz
Frequency Range: 524.500 MHz - 594.500 MHz
 30 channels in Handheld
 30 channels in Body Pack

Dual Channel Receiver GTU-DREC:

Controls: On-Off Power Switch
Audio Output: 1/4" Output
Power Supplied By: Lithium Ion Battery (Included)
 Mini USB Charging Input
Indicators: Power and Pairing Indicator LEDs
Receiving Sensitivity: < 2uV
Spurious Rejection: > 40dB
Audio output Impedance: 600 Ohm
Audio output Level: 0-0.5V
Input Power: 5VDC USB
Dimensions: 4.5" x 1.4" x 1" (114.3x35.5x25.4 mm)(HxWxD)
Weight: 2.8oz (79 g) with battery

Transmitters:

GTU-HH28 Handheld

GTU-MBP28 Body Pack

Controls: On-Off Power Switch / Volume Control / Channel Select
GTU-HH28 Handheld Mic Element: Dynamic Cardioid Capsule
Indicators: Backlit Display Shows Battery Level, Frequency, Channel, & RF
Frequency Stability: +- 0.005%
RF power: <30mW
Spurious Rejection: > 40dB
Peak Deviation: +- 75Khz
Modulation: UHF
Power Supplied By: (2) AA Alkaline or Rechargeable Batteries (Not Included)
Handheld Dimensions: 9.75" x 2.06" x 2.06" (248x52x52 mm)(HxWxD)
Handheld Weight: 9.2 oz (261 g) (Without Batteries)
Body Pack Dimensions: 4.25" x 2.7" x 1.17" (108x68.5x30 mm)(HxWxD)
Body Pack Weight: : 2.4 oz (68 g) (Without Batteries)

Included Accessories:

1/4 inch to 1/8 inch Adapter
 USB Charging Cable



*Actual range depends on RF signal absorption, reflection, interference, and battery characteristics.

Specifications subject to change without notice.



SUPERIOR SOUND FOR YOU

601 E. Pawnee Wichita, KS 67211 316.263.2852 FAX 316.263.0642 www.galaxyaudio.com
 Distributed in Canada by Audio Distributors International (ADI) 1275 Newton, unit 6 Boucherville, QC J4B 5H2 Canada
 450.449.8177 FAX 450.449.8180