

SOUNDTUBE[®] STNet™ Switch II



Description: Rack mountable 16-port 40w PoE audio quality switch designed for use in Dante Networks. In addition to the 16 Ethernet ports, the STNet- Switch II includes two SFP ports that can be adapted to fiber or high speed Ethernet connections. The two SFP ports can be turned into a high speed optical fiber ports or copper Ethernet ports with the addition of a Gigabit SFP transceiver module.

Features:

- 16 port high power 40W PoE switch
- 2 SFP ports
- Compatible with any PoE or PoE+ devices
- Smart Switch technology
- Rack mount option 1-RU
- Designed for use on Dante Networks

Applications: The STNet Switch II is designed for use with SoundTube STNet IPD speakers. It guarantees 40w of PoE power to all 16 ports simultaneously.

SoundTube[®]

10661 Rene St
 Lenexa, KS 66215
 Phone: 913.663.5600
 Fax: 913.663.3200
 Toll Free: 855.663.5600
www.soundtube.com



STNET SWITCH II PRODUCT SPECIFICATIONS	
POWER REQUIREMENTS	110-240 VAC, 50/60 Hz
10M/100M/1G RJ45 PORT	16
100M/1G SFP PORT	2
PROPRIETY (PoE+ 40W)	Yes
IEEE802.af (PoE 15.4W)	Yes
IEEE802.3at (PoE+ 30W)	Yes
AVAILABLE PoE POWER	640W
OPERATING TEMPERATURE	0°C to 40°C
OPERATING HUMIDITY	10 to 90% RH
STORAGE TEMPERATURE	-20°C to 70°C
STORAGE HUMIDITY	10 to 90% RH
AC INPUT	100V-240V
HEIGHT	44 mm / 1.73 in
WIDTH	442 mm / 17.4 in
DEPTH	211 mm / 8.3 in
WEIGHT	3.5 kg / 7.71 lbs
CERTIFICATIONS	UL 60950-1 / IEC 60950-1 / CE / EN 55032:2015 +AC:2016, Class A CISPR 32:2015 +Cor 1:2016, Class A / AS/NZS CISPR 32:2015, Class A EN 61000-3-2:2014, Class A / EN 61000-3-3:2013 / EN 55024:2010 EN 55024:2010 +A1:2015 / 47 CFR FCC Part 15, Subpart B, Class A ICES-003:2016 Issue 6, Class A / ANSI C63.4:2014