# VERISMO

# FRESNEL RGBALC

## Full Color LED Fresnel + Zoom

## **RGBALC + HSIC Color Mixing**

Verismo<sup>™</sup> Fresnel RGBALC is ideal for a variety of applications including theater, video, and production studios thanks to its high output 300W RGBALC LED module. Its advanced RGBALC color mixing system offers many control options including 16-bit fine dimming for each individual RGBALC color, 2x dedicated HSIC (hue, saturation, intensity, color temperature) control modes, and direct access to 2400K-6500K white CCT presets.



The 200mm (8-inch) Fresnel lens produces a bright circular light with a soft edge, and the beam angle can be adjusted anywhere from 18°-65° using its DMX controllable motorized zoom. Userselectable dimming curves, dimming speed, and frequency mode settings are accessible from its easy-to-use 4-button OLED control menu, and this fixture offers a standard sized 10-inch single slot frame/barndoor holder (accessories not included).

### **Euminous Intensity**

Lux/Meter	2.5 Meter	5 Meter
18° (narrow beam)	7,031 Lux	2,464 Lux
65° (wide beam)	1,140 Lux	440 Lux





#### **Main Features**

- Light source: 300W RGBALC LED module
- RGBALC + HSIC color mixing
- CCT range and presets from 2400K-6500K
- 16-bit dimming, 4 selectable dimming curves
- Refresh rates (1000-8000 Hz)
- User selectable dimming speeds
- 18°-65° motorized zoom
- 1-25Hz strobe effects
- Fresnel lens: 200mm (8-inch)
- 10-inch single slot frame/barndoor holder
- Aluminum housing (black)
- PowerCON® TRUE1™ compatible in/out
- 3/5-pin male/female XLR input & output



Optical

300W RGBALC LED

18°-65° motorized zoom

CCT range and presets from 2400K-6500K

CRI: 96

Flicker-free resolution



Weight & Dimensions

17" x 12" x 18" (430 x 303 x 457 mm)

21 lbs. (9.5 kg)

 $[\dagger \downarrow \dagger]$ 

Control

Protocol: DMX, RDM

3/5-pin DMX in/out

8/9/10/11/18-channels

4-button menu with **OLED** display

DMX512. master/slave. standalone



Power + Current

100-240VAC, 50-60 Hz

Consumption: 294W 2.56A, PF: .99

PowerCON™ TRUE1compatible in/out



Warranty + Certifications

2-year limited warranty

cETLus certified













