VERISMO

Warm White LED Profile Spot

High CRI, 3200K Warm White

Verismo™ Profile WW is a 3200K warm white fixture, well suited for a variety of applications including theater, video, and production studios thanks to its 300W WW LED module. It is incredibly bright making it perfect for long distance throws, and it offers 1/2/3 or 4-channel DMX control with 16-bit dimming + strobe. It can efficiently help reproduce true colors in comparison with that of natural light thanks to its high CRI of 98.

Loaded with Features

There are 4x lens options available for the Verismo™ Profile with the choices of 19°, 26°, 36°, or 50° beam angle. Its 4-blade manually adjustable shutters can create custom shapes or complete blackout, and users can project images with use of its included B sized gobo holder. User-selectable dimming curves, dimming speed, and frequency mode settings are also accessible from its easy-to-use, 4-button OLED control menu.

Luminous Intensity

Lux/Meter	2.5 Meter	5 Meter
19° Lens	30,655 Lux	6,959 Lux
26° Lens	15,991 Lux	4,142 Lux
36° Lens	12,998 Lux	3,022 Lux
50° Lens	6,345 Lux	1,560 Lux



Main Features

- Light source: 300W WW LED module
- CCT: 3200K, CRI: 98
- 16-bit dimming, 4 selectable dimming curves
- Refresh rates (1000-8000 Hz)
- User selectable dimming speeds
- 4x manual framing shutters & manual focus
- 1-25Hz strobe effects
- Flicker-free resolution, perfect for video
- Gobo/pattern holder (B sized gobos)
- Aluminum housing (black)
- 19°, 26°, 36°, and 50° lens tubes (sold separately)
- PowerCON® TRUE1™ compatible in/out
- 3/5-pin male/female XLR input & output



Optical

300W WW LED

CCT: 3200K

CRI: 98

Flicker-free resolution



Weight & Dimensions

23.8" x 12.6" x 18" (604 x 320 x 458 mm)

25.4 lbs. (11.5 kg)

Control

 $[\dagger \downarrow \dagger]$

Protocol: DMX, RDM

3/5-pin DMX in/out

1/2/3 or 4-channel DMX

4-button menu with **OLED** display

DMX512. master/slave. standalone



Power + Current

100-240VAC, 50-60 Hz

Consumption: 288W 2.48A, PF: .99

PowerCON™ TRUE1compatible in/out



Warranty + Certifications

2-year limited warranty

cETLus certified













