

Overview

The YXL15SP offers our best ratio of power, performance and value for an active subwoofer enclosure. Providing 500 watts (1000 watts peak) with efficient speaker components, the YXL Series is extremely loud for its size.

Features

- 1000 Watts (Peak) 500 Watts (Program)
- 15-inch woofer with 3-inch voice coil
- DSP processing with component protection
- Master Level control with Activity indicator
- 3 Performance modes, Punch, Smooth and Deep
- Recessed control panel



Specifications

System Type	Subwoofer
Powered or Passive	Powered
Power Rating (watts)	1000 watts peak
	500 watts program
Max SPL (dB)	128dB continuous
Frequency Response (Hz +/- 3dB)	45 - 100Hz
Crossover Frequency (Hz)	100Hz
LF Woofer	15″ (3″ Voice Coil)
LF Amplifier Type	Class D
Cooling Scheme	Speed Controlled Fan
Power Cable	Yes (Detachable IEC)
Level Controls	Master
EQ Controls	Pushbutton select,
	Punch, Smooth, Deep
Inputs	2 x Combijack (XLR/1/4″)
Outputs	2 x LINK (XLR Male)
Bar Handles	2 x Side
Pole Mount Adapter (13/8-inch/3.5cm)	1 Top
Enclosure Materials	12mm Plywood
Grille	Powdered Coated
	Perforated Steel
Covering / Finish	Textured Paint
Dimensions (DWH xbackW, inches)	19 x 18 x 24
Dimensions (DWH xbackW, cm)	48 x 46 x 61
Weight (lbs/kg)	62/28.1
Box Dimensions (LxWxH, inches)	25 x 25 x 29
Box Dimensions (LxWxH, cm)	63 x 63 x 74

Specifications subject to change without notice



