



LP-4VP-072

# Installation Guide

## LP-4VP-072 Package Contents

- 1 LT-803-072 Stationary 3-Channel FM Transmitter
- 1 LA-207 12 VDC Power Supply and Line Cord
- 1 LA-123 90 Degree Helical Antenna (72 MHz)
- 4 LR-3200 RF Receivers
- 4 LA-161 Single Ear Bud
- 1 LA-304 Assistive Listening Notification Signage Kit

## Setting Up the Transmitter



### 1. Plug the antenna into the back of the transmitter

### 2. Plug the audio source into audio input

The LT-803-072 accepts a balanced XLR or 1/4" (TRS), an unbalanced pair of RCA (phono) connectors or both.

### 3. Set the input switches to match the input gain

Input 1 accepts either a line, mic, or mic with phantom power. Input 2 can be adjusted to match the audio level coming in (-10 dBu or +10 dBu).

### 4. Connect the AC power to the unit

## Adjusting the Transmitter



**5. Press the power button to turn the unit on**

**6. Turn the Audio Level Input knob to adjust input to 1, 2, or both**

**7. Turn the Mix Level knob to adjust the mix level**

Note: Both the transmitter & receivers are defaulted to channel E

## Setting Up the Receivers



### 1. Power

To turn on the receiver, hold the power button for one second.

### 2. Plug in Headset

### 3. Adjust Volume

To desired level.

The receiver is charged with a micro USB charging cable provided with the system. When connected to the charger, a blinking light indicates it is being charged and a solid light indicates a full charge.



**LISTEN TECHNOLOGIES** 14912 Heritage Crest Way, Bluffdale, Utah 84065-4818 USA

**Phone:** +1.801.233.8992 **Toll-Free:** 1.800.330.0891 **[www.listentech.com](http://www.listentech.com)**

Copyright © 1998 - 2019 Listen Technologies Corporation. All rights reserved. 02142019-V1