

INSTALLATION INSTRUCTIONS NEPTUNE (Black/White)

Mounting plate 1 each
Mounting screw 2 each
Flat washer 2 each
Speaker 1 each

- 1) When mounting speakers, use the mounting plate as a template for marking and drilling the holes if being used on a solid surface or beam. If the unit is being attached to a single or double outlet gang box you will not need to mark your hole locations. (See figure 1)
- 2) If mounting onto the wall please use the guide plate on the bottom for alignment. To be sure you are straight use the level or horizon line inside the speaker to make sure you are level. (See figure 1)




Figure 1

- 3) If mounting to a ceiling please use at least 4 screws to attach the bracelet to the mounting surface
- 4) Assemble mounting screws and flat washers to attach mounting plate to single or double gang box already mounted in the ceiling or wall. Note that: Screws and washers provided are for mounting the mounting plate from both sides of the mounting location. For any other type of mounting, please consult your local hardware store for appropriate mounting screws.
- 5) Follow installation directions included with your amplifier (or receiver). Strip 1/2" (12mm) of insulation from each of the two conductors of the wire to expose the bare metal and twist each into a single strand. [Connect the speaker wire to the binding posts using the (+) as RED and the (-) as the BLACK] and hand tighten the binding posts accordingly. (See figure 2)
- 6) Set tap to desired wattage to 8 ohms or 25/70/100 volt tap setting for the power of amplifier (See figure 2)

7) Insert the speaker on the mounting bracket. Aligning the bottom of the speaker with the alignment guide inside the bracket and the speaker will snap into place if done correctly and not wires are in the way of the speaker cabinet. (See figure 3)

8) Insert and tighten the two screws on each side of the speaker cabinet to securely hold the speaker. (See figure 3)



Figure 2




Figure 3