

AMPLIFIED SURFACE MOUNT SINGLE SPEAKER AMP602B / AMP602W

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA



GENERAL SPECIFICATIONS

MODEL NUMBER: AMP602B / AMP602W	
DESCRIPTION:	6.5" active
OUTDOOR:	NO
IMPEDANCE:	4Ω
DISPERSION	92°
SENSITIVITY (1W/1M):	83 dB (VR at MAX)
POWER:	15W x 2
FREQUENCY RESPONSE:	80 Hz - 20 kHz
CROSS OVER:	3.5 K
S/N:	>80 dB
INPUT CONFIGURATION:	RCA L/R
INPUT LOAD IMPEDANCE:	20 KΩ
MAXIMUM CURRENT PROTECTED:	YES
ONE WIRE TO GROUND PROTECTED:	YES
SHORT CIRCUIT PROTECTED:	YES
THD:	<0.2%
POWER SUPPLY:	115V
HIGH FREQUENCY DRIVER:	1.5 kHz - 20 kHz
LOW FREQUENCY DRIVER:	80 Hz - 6 kHz
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Mica
TWEETER SIZE:	.79" (20 mm)
TWEETER MATERIAL:	PEI
ENCLOSURE:	High Impact Polystyrene (HIPS)
GIFT BOX DIMENSIONS (LxWxH):	19" x 11" x 13"
GIFT BOX WEIGHT	12 lbs
MASTER CARTON DIMENSIONS (LxWxH):	23" x 21" x 15"
MASTER CARTON QUANTITY:	2
WEIGHT	12 lbs. (5.5 Kg)
CE APPROVED:	Yes
COLOR/S:	white or black
PAINTABLE:	Yes
WARRANTY:	1 Year



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA
Tel: 310.515.1900
Toll Free: 800.638.1694
Fax: 310.515.1606
Web: www.owi-inc.com
E-mail: info@owi-inc.com

