

# AMPLIFIED SURFACE MOUNT

## Low Voltage Speaker Combination

### AMPLV6022B / AMPLV6022W

ARCHITECTS AND ENGINEERS  
SPECIFICATIONS / TECHNICAL DATA



#### GENERAL SPECIFICATIONS

MODEL NUMBER: AMPLV6022B / AMPLV6022W	
DESCRIPTION:	1 each 6.5", 2-Way, Surface Mount Amplified Speaker and 1 each Non-amplified Speaker
OUTDOOR:	No
IMPEDANCE:	4Ω
DISPERSION:	92°
SENSITIVITY (1W/1M):	83 dB (VR at Max)
POWER:	15 W x 2
FREQUENCY RESPONSE:	80 Hz - 20 kHz
S/N:	>80dB
INPUT CONFIGURATION:	RCA L/R
INPUT LOAD IMPEDANCE:	20 KΩ
MAXIMUM CURRENT PROTECTED:	Yes
ONE WIRE TO GROUND PROTECTED:	Yes
SHORT CIRCUIT PROTECTED:	Yes
THD:	<0.2%
POWER SUPPLY:	15V DC, UL Listed, Level 5 (Energy Star)
HIGH FREQUENCY DRIVER:	1.5 kHz - 20 kHz
LOW FREQUENCY DRIVER:	80 Hz - 6 kHz
WOOFER SIZE:	6.5"
WOOFER MATERIAL:	Mica
TWEETER SIZE:	079"(20 mm)
TWEETER MATERIAL:	PEI
ENCLOSURE:	High Impact Polystyrene (HIPS)
WEIGHT:	12 lbs. (5.5 Kgs)
COLOR/S:	White or Black
PAINTABLE:	Yes
WARRANTY:	1 Year
GIFT BOX DIMENSIONS (LxWxH):	19" x 11" x 13"
GIFT BOX WEIGHT:	24 lbs.
MASTER CARTON DIMENSIONS (LxWxH):	23" x 21" x 15"
MASTER CARTON QUANTITY:	4



#### OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA  
Tel: 310.515.1900  
Toll Free: 800.638.1694  
Fax: 310.515.1606  
Web: www.owi-inc.com  
E-mail: info@owi-inc.com

