

SELF-AMPLIFIED SURFACE MOUNTED SPEAKER COMBOS

AMP6022

(1) EACH SELF-AMPLIFIED SPEAKER WITH A 115 VOLT POWER SUPPLY AND (1) EACH NON-AMPLIFIED SPEAKER P602

AMPLV6022

(1) EACH SELF-AMPLIFIED, LOW VOLTAGE SPEAKER WITH A UL LISTED, 15 VDC, LEVEL **V** POWER SUPPLY AND (1) EACH NON-AMPLIFIED SPEAKER P602



PERFECT FOR SCHOOLS, HOTELS, CONFERENCE ROOMS AND TRAINING ROOMS.

AMP6022 (High Voltage Combo)
Self-Amplified Speaker with a
115 Volt Power Supply and
a Non-Amplified Speaker P602



AMP602W CE P602W

AMPLV6022 (Low Voltage Combo)
Self-Amplified Speaker with a
Low Voltage 15 VDC, Level **V** Power
Supply and a Non-Amplified Speaker P602



AMPLV602B CE P602B

FEATURES:

- Two Speakers – 6.5" Woofer Active (Self-Amplified) and Passive
- 15 Watts x 2 = 30 Watts Power
- 0.79" (20mm) Tweeter
- Impedance: 4 Ω
- Dispersion: 92°
- "U" Mounting Bracket Included
- CE Approved
- Weight: 12 Lbs. (Amplified)
10 Lbs. (Non-Amplified)
- Dimensions: 9.5"H x 8.46"W x 11.3"D
(242 x 215 x 288 mm)
- White or Black (Paintable)
- Sold as "Each" or in Combo
- 1 Year Warranty

OWI[®]
OWI Incorporated
Established 1978

SELF-AMPLIFIED SURFACE MOUNTED SPEAKER COMBOS

AMP6022

(1) EACH SELF-AMPLIFIED SPEAKER WITH A 115 VOLT POWER SUPPLY AND (1) EACH NON-AMPLIFIED SPEAKER P602

AMPLV6022

(1) EACH SELF-AMPLIFIED, LOW VOLTAGE SPEAKER WITH A UL LISTED, 15 VDC, LEVEL **V** POWER SUPPLY AND (1) EACH NON-AMPLIFIED SPEAKER P602

PASSIVE SPEAKER MODEL: P602

Description: 6.5" Passive Cabinet Speaker
 Outdoor: No
 Impedance: 4 Ω
 Dispersion: 92°
 Sensitivity (1W / 1M): 86 dB
 Maximum Power: 30 W
 Nominal Power: 15 W
 Frequency Response: 80 Hz - 20 kHz
 Crossover: 3.5 kHz
 High Frequency Driver: 1.5 kHz - 6 kHz
 Low Frequency Driver: 80 Hz - 6 kHz
 Woofer Size: 6.5"
 Woofer Material: Mica / Foam Surround
 Tweeter Size:79" (20 mm)
 Tweeter Material: PEI
 Enclosure: Plastic Enclosure
 Dimensions (LxWxH): 9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)
 CE Approved: Yes
 Weight (Pounds/Kgs): 10 lbs. (4.5 Kgs)
 Colors: White or Black
 Paintable: Yes
 Warranty: 1 Year



AMP602W **CE** Backside

P602W



AMPLV602B **CE** Backside

P602B

AMP6022 (High Voltage Combo)

Self-Amplified Speaker with a 115 Volt Power Supply and a Non-Amplified Speaker P602

AMPLV6022 (Low Voltage Combo)

Self-Amplified Speaker with a Low Voltage 15 VDC, Level **V** Power Supply and a Non-Amplified Speaker P602

AMPLIFIED SPEAKER MODEL: AMP602

Description: 6.5" Active
 Outdoor: No
 Impedance: 4 Ω
 Dispersion: 92°
 Sensitivity (1W / 1M): 83 dB (VR at Max.)
 Power: 15 W x 2
 Frequency Response: 80 Hz - 20 kHz
 Crossover: 3.5 kHz
 S / N: >80 dB
 Input Configuration: RCA L / R
 Input Load Impedance: 20 K Ω
 Maximum Current Protected: Yes
 One Wire To Ground Protected: Yes
 Short Circuit Protected: Yes
 THD: <0.2%
 Power Supply: 115 V
 High Frequency Driver: 1.5 kHz - 20 kHz
 Low Frequency Driver: 80 Hz - 6 kHz
 Woofer Size: 6.5"
 Woofer Material: Mica
 Tweeter Size:79" (20 mm)
 Tweeter Material: PEI
 Enclosure: High Impact Polystyrene (HIPS)
 Dimensions (LxWxH): 9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)
 Weight (Pounds/Kgs): 12 lbs. (5.5 Kgs)
 CE Approved: Yes
 Colors: White or Black
 Paintable: Yes
 CE Approved: Yes
 Warranty: 1 Year

AMPLIFIED SPEAKER MODEL: AMPLV602

Description: 6.5", 2-Way, Active, Full Range
 Outdoor: No
 Impedance: 4 Ω
 Dispersion: 92°
 Sensitivity (1W / 1M): 83 dB (VR at Max.)
 Power: 15 W x 2
 Maximum Power: 30 W
 Nominal Power: 15 W
 Frequency Response: 80 Hz - 20 kHz
 S/N: >80 dB
 Input Configuration: RCA L/R
 Input Load Impedance: 20 K Ω
 Maximum Current Protected: Yes
 One Wire to Ground Protected: Yes
 Short Circuit Protected: Yes
 THD: <0.2%
 High Frequency Driver: 1.5 kHz - 20 kHz
 Low Frequency Driver: 80 Hz - 6 kHz
 Woofer Size: 6.5"
 Woofer Material: Mica
 Tweeter Size:79" (20 mm)
 Tweeter Material: PEI
 Enclosure: High Impact Polystyrene (HIPS)
 Grill Material: FE
 Dimensions (LxWxH): 9.5 x 8.46 x 11.3" (242 x 215 x 288 mm)
 Weight (Pounds/Kgs): 12 lbs. (5.5 Kgs)
 Colors: White or Black
 Paintable: Yes
 Power Supply: 15 VDC, UL Listed, Efficiency Level **V** (Energy Star)
 (Dimensions: 4.7"H x 2.0"W x 1.2"D)
 CE Approved: Yes
 Warranty: 1 Year



AMP6022 (High Voltage Combo)



AMPLV6022 (Low Voltage Combo)