

IN CEILING SPEAKER: 2-IN-1

8" FULL RANGE, 8 OHMS/25V/70V/100V

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA

GENERAL SPECIFICATIONS



MODEL NUMBER:	ICM8
Description:	Full Range, 8" InCeiling 25V/70V/100V 100W Switchable SUB/HC
Impedance:	8Ω or 25V / 70V / 100V
25 Volt Taps:	13W, 6.3W, 3.1W, & 1.6W
70 Volt Taps:	100W, 50W, 25W, & 13W
100 Volt Taps:	100W, 50W, & 25W
8 Ohms Tap	YES
Sensitivity (1W/1M):	91dB
Max Power:	200W
Nominal Power:	100W
Frequency Response:	80Hz ~ 17KHz (-3dB) / 55Hz ~ 20KHz (-10dB)
Crossover:	Full Range(1.8KHz) / 125Hz / 6KHz
Dispersion (Coverage):	112°
Input Connection:	Removable locking connector with screw-down terminals. 2 input terminals and 2 loop-thru output terminals. Max. wire 12 AWG (2.5 mm ²)
Woofers Size:	8" Dia.
Woofers Material:	Paper Cone-Coated
Tweeter Size:	1" Dia.
Tweeter Material:	Silk Dome Tweeter
Grill Material:	Aluminum
Dimensions (HxWxD)	11" x 13" x 13"
Cut Out Size:	11 3/4"
Mounting Hardware:	YES
Mounting Bracket:(Included)	YES
Paintable:	YES
Outdoor rated:	NO
Covered Outdoor:	Yes



OWI Incorporated
17141 Kingsview Avenue, Carson, CA 90746 USA
Tel: 310.515.1900
Toll Free: 800.638.1694
Fax: 310.515.1606
Web: www.owi-inc.com
E-mail: info@owi-inc.com

