

BATHROOM SHOWER KITCHEN SPEAKER (BSK)

4" DUAL CONE, 4 OHMS

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA

GENERAL SPECIFICATIONS



MODEL NUMBER:	M4F
DESCRIPTION:	4", Water Resistant, Dual Cone Speaker
POWER HANDLING CAPACITY:	Nominal 15 W, Max 30 W
IMPEDANCE:	4 Ohms
WOOFER SIZE/MATERIAL:	4" / PPM with Cloth Surround
ENCLOSURE:	ABS Plastic (94V0)
FREQUENCY RESPONSE:	125 Hz - 20 kHz
SENSITIVITY (1W/1M)	85.6 dB
MAX SPL:	93 dB
DISPERSION:	120°
HUMIDITY:	To be normal (40 ± 2°C, Hum. 90-96% 144H)
HEAT TEST:	To be normal (70 ± 2°C, 30H)
COLD TEST:	To be normal (-25 ± 2°C, 48H)
DIMENSIONS (H x W x D)	4.55" x 4.55" x 2.2" (115.5 x 115.5 x 56mm)
HOLE CUT OUT (APPROX.)	4 1/32" (102 mm) Diameter
NET WEIGHT:	1.1 lbs. (0.5 kg)
COLOR:	White



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: www.owi-inc.com

E-mail: info@owi-inc.com



BATHROOM SHOWER KITCHEN SPEAKER (BSK)

4" DUAL CONE, 25/70/100 VOLTS

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA

GENERAL SPECIFICATIONS



MODEL NUMBER: M4F710	
DESCRIPTION:	4", Water Resistant, Dual Cone Speaker
POWER HANDLING CAPACITY:	Max 10 W
25 V TRANSFORMER POWER TAPS	0.08, 0.16, 0.31, 0.6, 1.25 W
70 V TRANSFORMER POWER TAPS	0.6, 1.25, 2.5, 5, 10 W
100 V TRANSFORMER POWER TAPS	1.24, 2.5, 5, 10 W
IMPEDANCE:	25/70/100 Volts & 4 Ohms
WOOFER SIZE/MATERIAL:	4" / PPM with Cloth Surround
ENCLOSURE:	ABS Plastic (94V0)
FREQUENCY RESPONSE:	125 Hz - 20 kHz
SENSITIVITY (1W/1M)	85.6 dB
MAX SPL:	93 dB
DISPERSION:	120°
HUMIDITY:	To be normal (40 ± 2°C, Hum. 90-96% 144H)
HEAT TEST:	To be normal (70 ± 2°C, 30H)
COLD TEST:	To be normal (-25 ± 2°C, 48H)
DIMENSIONS (H x W x D)	4.55" x 4.55" x 3.86" (115.5 x 115.5 x 98mm)
HOLE CUT OUT (APPROX.)	4 1/32" (102 mm) Diameter
NET WEIGHT:	1.51 lbs. (0.7 kg)
COLOR:	White



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: www.owi-inc.com

E-mail: info@owi-inc.com



BATHROOM SHOWER KITCHEN SPEAKER (BSK)

4" DUAL CONE, 25/70/100 VOLTS

ARCHITECTS AND ENGINEERS
SPECIFICATIONS / TECHNICAL DATA

GENERAL SPECIFICATIONS



MODEL NUMBER: M4F725	
DESCRIPTION:	4", Water Resistant, Dual Cone Speaker
POWER HANDLING CAPACITY:	Max 25 W
25 V TRANSFORMER POWER TAPS	0.62, 1.25, 1.88, 2.5, 3.1 W
70 V TRANSFORMER POWER TAPS	5, 10, 15, 20, 25 W
100 V TRANSFORMER POWER TAPS	10, 20 W
IMPEDANCE:	25/70/100 Volts & 4 Ohms
WOOFER SIZE/MATERIAL:	4" / PPM with Cloth Surround
ENCLOSURE:	ABS Plastic (94V0)
FREQUENCY RESPONSE:	125 Hz - 20 kHz
SENSITIVITY (1W/1M)	85.6 dB
MAX SPL:	93 dB
DISPERSION:	120°
HUMIDITY:	To be normal (40 ± 2°C, Hum. 90-96% 144H)
HEAT TEST:	To be normal (70 ± 2°C, 30H)
COLD TEST:	To be normal (-25 ± 2°C, 48H)
DIMENSIONS (H x W x D)	4.55" x 4.55" x 3.86" (115.5 x 115.5 x 98mm)
HOLE CUT OUT (APPROX.)	4 1/32" (102 mm) Diameter
NET WEIGHT:	1.51 lbs. (0.7 kg)
COLOR:	White



OWI Incorporated

17141 Kingsview Avenue, Carson, CA 90746 USA

Tel: 310.515.1900

Toll Free: 800.638.1694

Fax: 310.515.1606

Web: www.owi-inc.com

E-mail: info@owi-inc.com

