

Rogue Outcast 2 Beam



SPECIFICATIONS

Optical

- Light Source: 300W NSL Ushio lamp, 8000 K (color temp), 8,000 hours life expectancy
- Color Temperature (at full): 7353 K
- Front lens diameter: 160 mm
- CRI: 75.5
- Beam Angle: 0.8°
- Field Angle: 1.6°
- Cutoff Angle: 2°
- Lumens - Output: 29,130
- Illuminance (total) : 204,855 lux @ 15 m

Dynamic Effects

- Pan and Tilt: 540°/260°
- Pan and Tilt Ranges: 540°, 360°, 180° pan/260°, 180°, 90° tilt
- Colors: 14 + white, split colors, continuous scroll at variable speeds
- Gobos: 17 + open (17 metal), 17 static, continuous scroll at variable speeds; size: 106 mm (outside), 6 mm (image), 0.6 – 0.8 mm (max. thickness)
- Dimmer: Electronic
- Shutter/Strobe: Motorized
- Focus: Motorized
- Frost: Motorized
- Prism: 5 Facets, motorized, rotating
- Prism: 8 Facets, motorized, rotating
- Move-in-Black: Yes

FEATURES

- Fully featured, IP65 rated, high powered Beam fixture with an Ushio 300 W, 8,000 hour life expectancy lamp, 1 gobo wheel, 2 layerable prisms, precision focus, and lightweight aluminum/magnesium housing
- Individually controllable and layerable 5 facet linear and 8 facet round prisms for maximizing visual impact
- Frost for even light distribution
- Tight 0.8° narrow beam angle for focused air effects and no field spill
- 17 static gobos for massive visual effect
- DMX and RDM protocol control
- True 1 compatible power input
- Easy to read OLED display with simple, effective menu options
- Simple and complex DMX channel profiles for programming versatility
- USB-C port for uploading software

Optional Accessories

- Clamps
- IP65 5 pin DMX Cables
- IP65 PowerKon Extension cables
- Flight Case

Construction / Physical

- Dimensions: 14.41 x 9.61 x 22.6 in (366 x 244 x 574 mm)
- Weight: 45.19 lb (20.5 kg)
- Exterior Color: Black
- Housing Material: Aluminum/Magnesium diecast

Connections

- Power Connection: Edison plug to Seetronic Powerkon IP65
- Power Input: Seetronic Powerkon IP65
- Data Connectors: 5-pin IP rated
- Cable Length (power): 5 ft (1.5 m)

Control

- Control Protocol: DMX, RDM
- DMX Channels: 16 or 18

- Modes/Personalities: 2 personalities (16, 18)

Electrical

- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 413 W, 3.51 A @ 120 V, 60 Hz
- Power and Current: 403 W, 2.01 A @ 208 V, 60 Hz
- Power and Current: 404 W, 1.82 A @ 230 V, 50 Hz

Certifications / Qualifications

- CE, MET, UKCA
- IP Rating: IP65, temporary outdoor/ wet, with pressure equalizing M12 GORE valve
- Temperature (Ambient): -14 °F to 113 °F (-10 °C to 45 °C)
- Maximum Exterior Surface Temperature (Tc): 80° C / 176° F
- Maximum Ambient Temperature (ta): 45° C / 113° F

What's Included

- Rogue Outcast 2 Beam
- Seetronic Powerkon IP65 power cord
- (2) Omega brackets with mounting hardware