

DATA SHEET

PARLÉ™ SBC 2

SPEAKER BAR



The Parlé SBC 2 is a high fidelity speaker bar for use with conferencing systems. Intended for huddle rooms or small conference rooms, the SBC 2 is equipped with two 4” woofers and two 1” tweeters. It can be table- or wall-mounted. The SBC 2 supports several different options for audio input and can be integrated with a control system through an RS-232 port. It has three built-in EQ presets (Music, Video Conference, Presentation) switchable on the back of the speaker bar to provide clear and precise audio in different application settings.

FEATURES

- Equipped with two 4” woofers and two 1” tweeters
- Four audio input options: HDMI ARC, USB, Euroblock, and RCA
- Can be integrated with a control system via RS-232
- Includes wake-on-signal capability
- 3 built-in EQ presets
- Covered by Biamp Systems’ five-year warranty

ARCHITECTS & ENGINEERS SPECIFICATIONS

The speaker bar shall be designed to work with conferencing systems. The speaker bar shall be equipped with two 4-inch (102 mm) treated paper low frequency transducers (“woofers”) and two 1-inch (25 mm) high frequency transducers (“tweeters”). The high frequency transducer shall be physically separate from the low frequency transducer. The speaker bar shall be equipped with a five-position, 5.08 mm (0.2 inches) pluggable Euroblock connector, a USB 2.0 type-B connector, and two RCA connectors for audio signal connections. The speaker bar shall be equipped with one High-Definition Multimedia Interface (HDMI®) port with integrated support for Audio Return Channel (ARC). The speaker bar shall be equipped with a bi-directional RS-232 port. The speaker bar shall be equipped with wake-on-signal functionality. The speaker bar shall be CE marked, UL listed, and compliant with the RoHS directive. Warranty shall be five years. The speaker bar shall be the Parlé™ SBC 2.

PARLÉ SBC 2 SPECIFICATIONS

Unbalanced Input		RS-232:	19200/8-N-1
Number of Inputs:	1 (stereo)	USB:	
Connector:	RCA	Connector:	USB 2.0 Type-B
Input Impedance:	< 20kΩ	Codec:	24-bit PCM stereo
Max Input Level:	1 Vrms	Sample Rate:	44.1/48 kHz
Wake on Signal:	Yes	Power Consumption (100-240VAC 50/60Hz):	< 60W
Output		Overall Dimensions:	
Rated Power:	4 x 20 Wrms	Height:	5.1 inches (130 mm)
THD+N (20 Hz - 20 kHz, @ 1W):	< 0.1 %	Width:	40.1 inches (1018 mm)
Frequency Response (50 Hz - 20 kHz):	± 3 dB	Depth:	3.0 inches (75 mm)
Maximum SPL:	106 dBA	Weight:	9.9 lbs (4.5 kg)
HDMI:		Compliance:	
Supported Version:	1.4		CE Marked (Europe)
CEC Support:	Yes		RoHS Directive (Europe)
Codec:	24-bit PCM stereo		
Sample Rate:	44.1/48 kHz		

PARLÉ SBC 2 REAR PANEL



Biamp and Parl  are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. HDMI, HDMI High-Definition Multimedia Interface, and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.