

DATA SHEET

DEVIO® SCR-10

CONFERENCEING HUB



The Devio SCR-10 provides users with exceptional AV experiences when using conferencing systems. Intended for huddle rooms or small conference rooms, the Devio SCR-10 is a BYOD approach that supports a variety of room designs for computer-based conferencing. Devio works in concert with PCs running a variety of conferencing solutions including Microsoft Teams, Zoom, BlueJeans, Google Meet, and many more.

FEATURES

- Works in concert with PCs running conferencing solutions, including Microsoft Teams, Zoom, BlueJeans, Google Meet, and many more
- Supports both Windows and Mac PCs, and uses standard audio drivers
- Single cable solution (USB) for BYOD
- Supports connections for up to 3 USB and 2 analog peripheral devices
- Includes support for CEC and wake-on-signal technology to control a connected display
- CE marked, UL listed, and RoHS compliant
- Covered by Biamp Systems' three-year warranty

ARCHITECTS & ENGINEERS SPECIFICATIONS

The conferencing hub shall be designed to connect soft codec conferencing systems with in-room audio and video devices. The conferencing hub shall connect to a Windows® or Mac OS X computer via a Universal Serial Bus (USB) connection using a standard USB type B connector. The conferencing hub shall be equipped with one USB 3.0 type A port and two USB 2.0 type A ports. The conferencing hub shall be able to receive and transmit audio streams over USB via a USB Class 1 Audio device. The conferencing hub shall be equipped with one High-Definition Multimedia Interface (HDMI®) port to connect a monitor to a BYOD computer using DisplayLink USB graphics technology. The conferencing hub shall be equipped with one 3.5mm jack for analog stereo audio input and one 3.5mm jack for analog stereo audio output. The conferencing hub shall be CE marked, UL listed, and compliant with the RoHS directive. Warranty shall be three years. The conferencing hub shall be the Devio® SCR-10.

DEVIO SCR-10 SPECIFICATIONS

Network Connection:	RJ-45 with Ethernet cable (Cat 5e and above)	Overall Dimensions:	
Status Indicators:	Status Indicator (Green/Red LED)	Height:	0.9 inches (23 mm)
Video:		Width:	7.3 inches (185 mm)
Supported Resolutions:	Up to 4096 x 2160p (60fps)	Depth:	3.3 inches (85 mm)
Physical Interface:	HDMI	Weight:	0.4 lbs (200 g)
HDCP Support:	2.0	Included Accessories:	3m USB 3.0 cable Mounting screws Zip ties
Power:	5V DC 15W	Environmental:	
		Ambient Operating Temperature Range:	50-86° F (10-30° C)
		Humidity:	10-90% relative humidity (non-condensing)
		Compliance:	CE Marked (Europe) RoHS Directive (Europe)

DEVIO SCR-10 FRONT PANEL



Biamp and Devio are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. HDMI, HDMI High-Definition Multimedia Interface, and the HDMI logo are either trademarks or registered trademarks of HDMI Licensing LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.



A: 9300 S.W. Gemini Drive Beaverton, OR 97008 USA

T: +1 503.641.7287

W: www.biamp.com

DEVDS-517-2111-EN-R1