

(Lens Sold Separately)

ENCORE PROFILEMINI COLOR

Designed for applications where size really matters, the ADJ Lighting Encore Profile Mini Color is a compact and versatile LED-powered color ellipsoidal luminaire. It utilizes a versatile LED engine comprised of 16 x 3.5W RGBWAL (red / green / blue / white / amber / lime) LEDs that offers a 50,000-hour average life expectancy. Through varying the intensity of the six LED colors, an extremely wide color palette can be achieved, ranging from vibrant and bold primaries to soft and subtle pastels. It can also generate white light with color temperatures varying from 2700K up to 7000K, with a dedicated Dynamic White DMX channel provided to allow simple selection.

Two compatible lens options are available (sold separately), which can be used to adapt the fixture depending on the beam angle required. Both lenses offer manual zoom, with the EP Mini Lens 1530 option offering a variable beam angle of 15° - 30° and the EP Mini Lens 2550 version providing wider options of 25° - 50°. The fixture can also be used to project GOBO patterns and is supplied with a holder for standard "E" size GOBOs (GOBOs sold separately).

The Encore Profile Mini Color offers digital dimming with variable curves and a selection of dimming modes as well as variable speed strobing. It also supports adjustable refresh rates so that flicker can be avoided for filming applications. A convenient OLED menu display on the rear panel provides access to an intuitive menu interface for DMX addressing and configuration of the unit's adjustable operating parameters and it is supplied with a variable angle hanging bracket that locks securely into place using a pair of large thumb tightening screws.

ENCORE PROFILE MINI COLOR



Light Source:

- 16x 3.5W RGBWAL (Red/Green/Blue/White/Amber/Lime) LED Engine
- 50,000 Hour Average LED Life*
- *LED Life may vary depending on several factors including but not limited to: Environmental Conditions, Power/Voltage, Usage Patterns (On-Off Cycling), Control, and Dimming.

Photometic Data:

•>86CRI 300 Total Lumens (4,200 CT)

Effects:

- Electronic Strobe and Dimming
- Variable Dimming Curves and Dimming Modes
- Independent dynamic white fader feature that achieves white color temperatures from 2700K to 7000K

GOBOs:

- Supports "E" Size GOBOs
- Metal Gobo Dimensions: Outer Diameter 45mm, Image Diameter 31mm
- Glass Gobo Dimensions: Outer Diameter 39.5mm, Image Diameter 31mm
- · Gobo Holder is included
- Gobo's are sold separately

Control / Connections:

- 3 DMX Channel Modes (6 / 8 / 12)
- Adjustable Refresh Rates (900-1500, 25,000 Hz)
- 4 Button Control Panel
- OLED Menu Display
- Locking 5-pin XLR Connector In/Out
- IP65 Locking Power In/Out
- With Wired Digital Communication Network
- RDM (Remote Device Management)
- USB Service Port

Dimensions & Weight:

- Length: 6.03" (153mm) (NO LENS)
- Width: 5.67" (144mm)
- Vertical Height: 10.75" (273mm)
- Weight: 3.64 lbs. (1.65 kg





LINEAR COLOR TEMPERATURE CONTROL (TUNABLE WHITE)



ENCORE PROFILE MINI COLOR



Electrical / Thermal:

- Convection Cooled
- AC 100-240V 47/63Hz
- 42.5W Max Power Consumption @ 120V
- Power Linking: 28pcs Max @120V / 57pcs Max @230V
- Minimum and Maximum Ambient Temperatures: 14° to 113°F (-10° to 45°C)

Approvals:

• CE | cETLus (Pending) | IP20

What's Included:

• 1 IP65 Locking Connector to Edison Power Cable

Optional Accessories:

- EP Mini Lens 1530 (15° 30° Manual Zoom Lens)
- EP Mini Lens 2550 (25° 50° Manual Zoom Lens)
- SIP064: 1.64ft. IP65 male to female twist lock power link cable
- SIP113: 3ft. IP65 male to female twist lock power link cable
- SIP126: 5ft. IP65 male to female twist lock power link cable
- SIP139: 10ft. IP65 male to female twist lock power link cable
- SIP152: 16ft. IP65 male to female twist lock power link cable
- SIP165: 25ft. IP65 male to female twist lock power link cable
- SIP178: 50ft. IP65 male to female twist lock power link cable
- SIP191: 100ft. IP65 male to female twist lock power link cable

Specifications subject to change without notice



EP Mini BDA (EPL153)Barn Door Assembly
Sold Separately





EP Mini Lens 1530 (EPL113) (15° - 30° Manual Zoom Lens) Sold Separately



EP Mini Lens 2550 (EPL126) (25° - 50° Manual Zoom Lens) Sold Separately