

# Motif™ risplendi. 150

## 150W, Full Color LED Pendant

### RGBAL Color Mixing

Motif™ Risplendi 150 is an ETL listed, full color architectural pendant light with a 150W RGBAL COB LED light source. It offers high CRI white and vivid mixed colors that can easily provide reading-level brightness when installed in high ceilings. It comes with a pre-installed 80° diffuser lens and 3 replaceable Fresnel lenses (30°, 45°, and 60°) for a variety of beam angles.

### Versatile & Adaptable

Its stylish aluminum housing comes in your choice of black, white, or space gray, and its mounting options include an adjustable yoke or a stable bracket for permanent vertical installations. It offers switchable power that includes a powerCON TRUE1™ compatible input and terminal block for hardwiring, plus it also has emergency power connections so you'll never be left in the dark.

### Luminous Intensity

Lux/Meter	2.5 Meter	5 Meter	7.5 Meter
35° Lens	5,658	1,488	732
45° Lens	4,303	1,160	594
60° Lens	2,785	754	364
80° Lens	1,208	353	163



### Housing colors:

- Black
- White
- Space Gray



Part# SNOOT-Motif Risplendi B, W, or SG (not included).

### Main Features

- Light source: 150W RGBAL COB LED
- Built-in color & chase macros via DMX
- Built-in automated programs via master/slave
- Color mixing ability in standalone mode
- 4x light collimating lenses (30°, 45°, 60°, 80°)
- Convection cooled aluminum housing
- Dual mounting brackets for positioning flexibility
- Adjustable LED refresh rates (1200Hz-20KHz)
- PowerCON® TRUE1™ compatible power input
- Hardwired AC power connections
- Power backup connector (42-48V DC, 20W)
- 5-pin XLR input & output connections
- 8.5 cm snoot, full shield attachment (sold separately)



#### Optical

150W RGBAL COB LED,  
100,000 hrs.

4x interchangeable light  
collimating lenses:  
30°, 45°, 60°, 80°

PWM refresh rates:  
1200Hz-20KHz



#### Weight & Dimensions

11.3" x 10.5" x 7.9" (287  
x 266 x 200 mm)

11.3 lbs. (5.1 kg)



#### Control

USITT DMX-512, RDM

5-pin DMX in/out

5/7/11-channel DMX

4-button menu with  
OLED display

DMX512, M/S, standalone,  
auto mode



#### Power + Current

100-240VAC, 50-60 Hz

Consumption: 141W,  
1.24A, PF: .98

PowerCON™ TRUE1-  
compatible input +  
hardwire connections



#### Warranty + Certifications

2-year limited warranty

cETLus certified



[www.blizzardpro.com](http://www.blizzardpro.com)

[info@blizzardpro.com](mailto:info@blizzardpro.com)

1.866.493.6025



Like



Watch



Follow