

IP65, Warm White LED Profile Spot

High CRI, 3200K Warm White

Verismo™ IP Profile WW is a 3200K warm white fixture, well suited for a variety of applications including theater, video, and production studios thanks to its 300W WW LED module. It is incredibly bright making it perfect for long distance throws, and it offers 1/2/3 or 4-channel DMX control with 16-bit dimming + strobe. It can efficiently help reproduce true colors in comparison with that of natural light thanks to its high CRI of 98.

Loaded with Features

There are 4x lens options available for the Verismo™ IP Profile WW with the choices of 19°, 26°, 36°, or 50° beam angle. Its 4-blade manually adjustable shutters can create custom shapes or complete blackout, and users can project images with use of its included B sized gobo holder. User-selectable dimming curves, dimming speed, and frequency mode settings are also accessible from its easy-to-use, 4-button OLED control menu.

Luminous Intensity

| Lux/Meter | 2.5 Meter | 5 Meter |
|-----------|------------|-----------|
| 19° Lens | 27,165 Lux | 7,421 Lux |
| 26° Lens | 13,336 Lux | 4,018 Lux |
| 36° Lens | 10,192 Lux | 3,813 Lux |
| 50° Lens | 6,500 Lux | 1,808 Lux |



Main Features

- Light source: 300W WW LED module
- CCT: 3200K, CRI: 98
- IP rating: IP65
- 16-bit dimming, 4 selectable dimming curves
- Refresh rates (1000-8000 Hz)
- User selectable dimming speeds
- 4x manual framing shutters & manual focus
- 1-25Hz strobe effects
- Flicker-free resolution, perfect for video
- Gobo/pattern holder (B sized gobos)
- 19°, 26°, 36°, and 50° lens tubes (sold separately)
- PowerCON® TRUE1™ compatible in/out
- 5-pin male/female XLR input & output



Optical

300W WW LED

CCT: 3200K

CRI: 98

Flicker-free resolution



Weight & Dimensions

25.6" x 12.6" x 18" (649 x 320 x 458 mm)

19 lbs. (8.6 kg)

 $[\dagger \downarrow \dagger]$

Control

Protocol: DMX, RDM

5-pin DMX in/out

1/2/3 or 4-channel DMX

4-button menu with **OLED** display

DMX512. master/slave. standalone



Power + Current

100-240VAC, 50-60 Hz

Consumption: 266W 2.36A, PF: .99

PowerCON™ TRUE1compatible in/out



Warranty + Certifications

2-year limited warranty

cETLus certified















