

VERISMO™ IP

PROFILE RGBALC

IP65, Full Color LED Profile Spot

RGBALC + HSIC Color Mixing

Verismo™ IP Profile RGBALC is ideal for a variety of applications including theater, video, and production studios thanks to its high output 300W RGBALC LED module. Its advanced RGBALC color mixing system offers many control options including 16-bit fine dimming for each individual RGBALC color, 2x dedicated HSIC (hue, saturation, intensity, color temperature) control modes, and direct access to 2200K-10000K white CCT presets.

Loaded with Features

There are 4x lens options available for the Verismo™ IP Profile with the choices of 19°, 26°, 36°, or 50° beam angle. Its 4-blade manually adjustable shutters can create custom shapes or complete blackout, and users can project images with use of its included B sized gobo holder. User-selectable dimming curves, dimming speed, and frequency mode settings are also accessible from its easy-to-use, 4-button OLED control menu.

Luminous Intensity

Lux/Meter	2.5 Meter	5 Meter
19° Lens	10,229 Lux	2,483 Lux
26° Lens	5,032 Lux	1,289 Lux
36° Lens	3,043 Lux	791 Lux
50° Lens	1,481 Lux	330 Lux



Main Features

- Light source: 300W RGBALC LED module
- RGBALC + HSIC color mixing
- IP rating: IP65
- CCT range and presets from 2200K-10000K
- 16-bit dimming, 4 selectable dimming curves
- Refresh rates (1000-8000 Hz)
- User selectable dimming speeds
- 4x manual framing shutters & manual focus
- 1-25Hz strobe effects
- Gobo/pattern holder (B sized gobos)
- 19°, 26°, 36°, and 50° lens tubes (sold separately)
- PowerCON® TRUE1™ compatible in/out
- 5-pin male/female XLR input & output



Optical

300W RGBALC LED
 RGBALC + HSIC color mixing
 CCT range and presets from 2200K-10000K
 CRI: 94
 Flicker-free resolution



Weight & Dimensions

25.6" x 12.6" x 18" (649 x 320 x 458 mm)
 21.2 lbs. (9.6 kg)



Control

Protocol: DMX, RDM
 5-pin DMX in/out
 7/8/9/10/17-channel DMX
 4-button menu with OLED display
 DMX512, master/slave, standalone



Power + Current

100-240VAC, 50-60 Hz
 Consumption: 289W
 2.56A, PF: .99
 PowerCON™ TRUE1-compatible in/out



Warranty + Certifications

2-year limited warranty
 cETLus certified



www.blizzardpro.com

info@blizzardpro.com

1.866.493.6025



Like



Watch



Follow