



SKB's new Rolling Roto Shock Racks feature a (20" deep) roto molded tough shell with an integrally molded valance that eliminates the need for a metal valance on the outside of the case.

## **FEATURES INCLUDE:**

■ Standard 19" rack width per EIA standards

■ Rack depth front to rear rail is 20" and each lid is 2-1/4" deep

■ Threaded steel rails and aluminum cross components forming an "H" shaped rigid configuration

 Recessed TSA trigger release latches allow for opening while stacked

 Secure stacking design allows full use of doors while racks are stacked together

 8 elastomeric shocks with a load range of from 40 lbs. to 150 lbs.)

 Load range may be increased up to 300 lbs. with optional additional HM-245 elastomeric shocks (see website for details)

- Gasket sealed front and rear doors
- Ambient pressure relief valve
- Sliding retractable handle
- Oversized snap-down handles on each side of the case
- Convenient roller blade wheels
- Cases stocked in Black
- Custom colors available (minimum quantities apply)

Standard dimensions - front to rear rail: 20"

	Part #	Rack Units	Height	Lid Depth
	3SKB-R04U20W	4 space	7"	2-1/4"
	3SKB-R06U20W	6 space	10-1/2"	2-1/4"
	3SKB-R08U20W	8 space	14"	3-1/4"
*	3SKB-R10U20W	10 space	17-1/2"	3-1/4"
*	3SKB-R12U20W	12 space	21"	3-1/4"

\* - Available Summer 2008





lastomers



relief valves

MUSIC PRODUCTS 800.410.2024 SPORTS PRODUCTS 800.654.5992

INDUSTRIAL PRODUCTS 800.783.0087

www.skbcases.com