

CVC-7WMTDV

Vandal-Resistant High Resolution Wall/Ceiling Mount Color Dome Camera with Auto Iris Varifocal Lens

Also available:

CVC-7WMTD standard resolution

- Wall or ceiling mounting through the use of a unique internal 3-way camera bracket
- Flush or surface mounting using the supplied surface mount adapter box
- Supplied with a tinted and clear "lined" dome to accommodate a wide range of lighting conditions
- Conduit compatible
- Safety strap holds dome cover in place while making adjustments
- Fits over a standard 2-gang box



Specifications

	CVC-7WMTDV	CVC-7WMTD
Horizontal Resolution	480 TV lines	380 TV lines
Image Device	1/3" Sony HAD advanced image sensor	1/4" CCD format
Min. Object Illumination	0.03 lux	1 lux
Effective Picture Element	470 K	210 K
Backlight Compensation	Active-Turbo	Active
Electronic Shutter	1/60-1/100,000 seconds	1/60-1/100,000 seconds
Built In Lens	DC auto iris varifocal lens 4-9mm, F1.6	4mm, optional lenses available
Video S/N Ratio	Greater than 50db	Greater than 48db
Weatherproof Standard	IP67	IP67
Operating Environment	-20°F to 122°F	-20°F to 122°F
TV Format	NTSC, color	NTSC, color
Video Signal Output	1.0Vp-p/75 ohms (BNC)	1.0Vp-p/75 ohms (BNC)
Power Consumption	200mA	110mA
Power Supply	24V AC @ 20 VA or 12V DC regulated power supply (UL & CSA listing) included	12V DC regulated power supply (UL & CSA listing) included
Weight	3.3 lbs	3.2 lbs



Specifications subject to change

For more information contact us at:

Speco Technologies 200 New Highway, Amityville, NY 11701 Web: www.specotech.com
Toll Free: 1-800-645-5516 In Metro NY: 631-957-8700 Fax: 631-957-9142 or 631-957-3880