



**25246B**

14/4 UTP CMP  
 Audio, Control, and Low Voltage Power

**Construction & Dimensions**

CONSTRUCTION & DIMENSIONS	
CONDUCTOR PARAMETER	
• Number of Conductors	4
• AWG Size	14
• Conductor Stranding	19x27
• Conductor Type	Bare copper
• Nominal DCR	2.7 Ohm/1000ft
• Cabling Lay Length	4.5 in
INSULATION PARAMETER	
• Insulation Type	Plenum PVC
• Insulation Thickness	0.012 in
• Insulation Color Code	1.Black,2.Red,3.White,4.Green
SHIELDING PARAMETER	
• Shield Type	None
ELECTRICAL CHARACTERISTICS	

**Overall Construction**

OVERALL CONSTRUCTION PARAMETERS	
Jacket Type	Flexible Plenum
Jacket Thickness	0.015 in
Nominal Cable O.D.	0.262 in
Plenum	Yes
NEC UL Rating	CL3P, FPLP
RoHS Compliant	Yes
Pull Tension	145 lbs
Bend Radius	2.358 in
Cable Weight	67 lbs

**Overall Electrical & Optical Characteristics**

OVERALL ELECTRICAL/OPTICAL CHARACTERISTICS	
UL Flammability	NFPA 262 Plenum
Operating Range	-0 to 60 Deg C
UL Voltage Rating	300

## Detailed Specification & Technical Data



### **25246B**

14/4 UTP CMP

Audio, Control, and Low Voltage Power

## Related Products

RELATED PRODUCTS	
Non Plenum Number	246
Aquaseal Direct Burial Number	AQ246
4 Pole SpeakOn	CN-NL4FC
SpeakOn Panel Mount	CN-NL4MP