

# Product data sheet

Specifications



## APC Smart-UPS On-Line, 2200VA, Tower, 120V, 6x 5-20R+1x L5-20R NEMA outlets, SmartSlot, Extended runtime, W/O rail kit

SRT2200XLA

**Product availability : Stock - Normally stocked in distribution facility**

### Overview

<b>Presentation</b>	High density, double-conversion on-line power protection with scalable runtime.
<b>Lead time</b>	Usually in Stock

### Main

<b>Main Input Voltage</b>	120 V
<b>Main Output Voltage</b>	120 V
<b>Kw Rating</b>	1800 W
<b>Rated power in VA</b>	2200 VA
<b>Input Connection Type</b>	NEMA 5-20P
<b>Output connection type</b>	6 NEMA 5-20R 1 NEMA L5-20R
<b>Cable length</b>	6 ft (1.83 m)
<b>Number of cables</b>	1
<b>Battery Type</b>	Lead-Acid battery
<b>Provided equipment</b>	CD with software Documentation CD Installation guide Removable support feet USB cable Warranty card

### Batteries & Runtime

<b>Included Battery Modules</b>	1
<b>Battery Slots Empty</b>	0
<b>Typical recharge time</b>	3 h
<b>RBC Quantity</b>	1
<b>Battery Voltage</b>	72V
<b>Battery Charge Power (Watts)</b>	102 W rated
<b>Battery power in VAh</b>	306 VAh runtime
<b>Battery Life</b>	3...5 year(s)
<b>Replacement battery</b>	<a href="#">APCRBC141</a>
<b>Battery option</b>	SRT72BP 1 918 VAh

SRT72BP 2 1530 VAh  
SRT72BP 3 2142 VAh  
SRT72BP 4 2754 VAh  
SRT72BP 5 3366 VAh  
SRT72BP 6 3978 VAh  
SRT72BP 8 5202 VAh  
SRT72BP 10 6426 VAh

---

Extendable Run Time	1
---------------------	---

## General

---

Product web sub-family	High density
------------------------	--------------

---

Number of power module	1400
------------------------	------

---

Number of power module free slots	0
-----------------------------------	---

---

Number of power module filled slots	0
-------------------------------------	---

---

Redundant	No
-----------	----

## Physical

---

Color	Black
-------	-------

---

Height	17.01 in (43.2 cm)
--------	--------------------

---

Width	3.35 in (8.5 cm)
-------	------------------

---

Depth	22.99 in (58.4 cm)
-------	--------------------

---

Net Weight	55.12 lb(US) (25 kg)
------------	----------------------

---

Mounting Location	Front
-------------------	-------

---

Mounting preference	Lower
---------------------	-------

---

Mounting Mode	Not rack-mountable
---------------	--------------------

---

Two post mountable	0
--------------------	---

---

USB compatible	Yes
----------------	-----

---

Mounting position	Vertical
-------------------	----------

## Input

---

Input Frequency	40 - 70 Hz auto-sensing
-----------------	-------------------------

## Output

---

Max Configurable Power (Watts)	1800 W
--------------------------------	--------

---

Harmonic distortion	Less than 2%
---------------------	--------------

---

Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains
----------------------------------	---------------------------------

---

Crest factor	3 : 1
--------------	-------

---

Topology	Double Conversion Online
----------	--------------------------

---

Waveform Type	Sine wave
---------------	-----------

---

Bypass type	Internal Bypass (Automatic and Manual)
-------------	--

---

Maximum configurable power in VA	2200 VA
----------------------------------	---------

## Conformance

---

Product Certifications	ENERGY STAR V2.0 (USA)
------------------------	------------------------

## Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 % non-condensing
Operating altitude	0...10000 ft
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 % non-condensing
Storage altitude	0...50000 ft (0.00...15240.00 m)
Heat dissipation	535 Btu/h
IP degree of protection	IP20

## Communications & Management

Free slots	1
Alarm	Audible and visible alarms : prioritized by severity
Emergency Power Off (EPO)	Yes

## Surge Protection and Filtering

Surge energy rating	340 J
---------------------	-------


## Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304325161
Returnability	No
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	9.69 in (24.6 cm)
Package 1 Width	31.89 in (81 cm)
Package 1 Length	23.58 in (59.9 cm)
Package 1 Weight	67.99 lb(US) (30.84 kg)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
ENERGY STAR®	<a href="#">ENERGY STAR UPS V2.0 (USA)</a> 
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>

---

<b>Environmental Disclosure</b>	<a href="#">Product Environmental Profile</a>
<b>Circularity Profile</b>	<a href="#">End of Life Information</a>
<b>Optimized Energy Efficiency</b>	Energy efficient product
<b>Take-back</b>	Take-back program available

---

## **Contractual warranty**

---

<b>Warranty</b>	3 years repair or replace (excluding battery) and 2 years for battery
-----------------	---

## **Recommended replacement(s)**