



# kramer

## VW-4

4 Output Video Wall Driver

| HDMI | Ethernet - RJ-45



VW-4 is a 4-output video wall driver designed to quickly and easily configure and manage video walls. Use one VW-4 device to create any wall configuration with up to 4 displays, for example, a 2x2, 4x1, 1x4, 2x1, 3x1 video wall. Connect additional devices to create walls of any size and configuration of up to 64 displays. Configure a single or multiple device setup using the VW-4 app via Ethernet or RS-232, or quickly configure a basic setup using the local dip switches

## FEATURES

**Scalable Video Walls** - Create and manage a video wall of up to 4 displays or, by adding devices, create video walls of up to 64 displays

**Quick, Basic, Local Setup** - Use front panel DIP-switches for basic setup of video walls up to 16 displays

**Full Feature Configuration** - Use the VW-4 app via Ethernet or RS-232 to set up video walls of up to 8x8 displays. Also use the app for the following: bezel corrections, HDCP status, factory reset, upgrading firmware, viewing network settings and copying EDID

**Content Protection** - Supports HDCP 2.2 on the input and loop output and HDCP 1.4 on the main outputs. HDCP can be disabled on the input

**EDID Support** - Upload EDID files, copy any output EDID to the input, and select from several built-in EDID files

**Reliable Video** - Features constant output sync and auto-sync off option that stops or delays the 5V shutoff when no input is detected

**Auto Display Powering** - CEC capabilities turn ON or OFF the connected displays according to the status of the input video

**Easy Installation** - Compact MegaTOOLS® fan-less enclosure for surface mounting or side-by-side mounting of 2 units in a 1U rack space with the recommended rack adapter



# kramer

## TECHNICAL SPECIFICATIONS

---

Inputs	1 HDMI: On a female HDMI connector
Outputs	4 HDMI: On female HDMI connectors 1 HDMI Loop: On a female HDMI connector
Ports	1 Ethernet: On an R-J45 connector 1 RS-232: On a 3-pin terminal block connector USB: On a USB type-A connector
Video	Max Input Resolution: 4K@60Hz (4:4:4) Max Input Data Rate: 18Gps Output Resolution: 1080p Content Protection on Input and Loop Output: HDCP 2.2 Content Protection on Main Outputs: HDCP 1.4
User Interface	Indicators: I/O detection and power LEDs Controls: DIP-switches for basic setup, computer app for comprehensive setup via Ethernet or RS-232, firmware upgrade via USB
Accessories	Included: Power adapter, bracket set, rubber feet
POWER:	
Power	Source: 5V DC Consumption: 2.9A
Environmental Conditions	Operating Temperature: 0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensing Storage Temperature: -20 to +70°C (-4 to + 158 °F), 10% to 90%, non-condensing Humidity: 10% to 90%, non-condensing
Product Dimensions	19.00cm x 19.50cm x 2.70cm (7.48" x 7.68" x 1.06" ) W, D, H
Product Weight	0.9kg (1.9lbs) approx
Shipping Dimensions	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83" ) W, D, H
Shipping Weight	1.4kg (3.1lbs) approx

