



**Specs**

**Warning**

**Warranty**

**Disclaimer**

**EMC / EMI**

## Specs

### Controls / Front

**Level:** Sets the volume of the overdriven signal.

**Drive:** Sets the amount of saturation in the overdriven signal.

### Controls / Back

Open the magnetic bottom lid to access the controls.

**Blend:** Mixes the clean input signal with the overdriven signal. The clean signal is fixed at unity gain, while the volume of the overdriven signal is set by the Level knob, allowing for fine control of the blend ratio. Turn clockwise to blend in the clean signal.

**Tone:** Controls the high frequency content of the sound. A variable low pass filter from 3 kHz to 8 kHz. Turn CCW for a brighter sound.

## DIP switches

**Grunt:** Provides a low-end boost to massively thicken your sound when engaged.

**MBoost:** Gives a subtle 6 dB boost from 300 Hz to 1 kHz to help you cut through the mix.

## Technical Specifications

**Input Impedance:** 1M $\Omega$

**Output Impedance:** 1k $\Omega$

**Current Consumption:** ~17mA

**Voltage:** 9V DC (Center Negative)

## Dimensions

**Width:** 50 mm / 2"

**Length:** 100 mm / 4"

**Height:** 45 mm / 1,75"

**Weight:** 205 g / 0,45 lb

## Warning

The Microtubes B1K has a current draw of 30mA. Only use a regulated 9V DC adapter with a center-negative plug. Unregulated power supplies and/or higher voltages may result in suboptimal noise performance and even damage your unit, voiding the warranty.

## Warranty

To activate the warranty, we encourage you to register your product on: <http://mypedal.darkglass.com> and enter the serial number on the back of your pedal. Please contact us via email [support@darkglass.com](mailto:support@darkglass.com) before shipping a product to us.

# Disclaimer

In the interest of continuous improvement, specifications are subject to change without notice. If you have any questions, please don't hesitate to contact us at [www.darkglass.com](http://www.darkglass.com). The manufacturer claims that the above product fulfills the requirements as set by EN55013, EN55020, EN60555-2, EN60555-3, RoHS, WEEE.

1176®, and SSL® are registered trademarks of their respective companies. Names of factory modes are intended for descriptive purposes only and should not be construed as an endorsement or affiliation with the companies or products named.

# EMC / EMI

This equipment has been tested and found to comply with the limits for a Class B Digital device, pursuant to part 15 of the FCC rules. These limits are designed to provide reasonable protection against harmful interference in residential installations.

This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. There is no guarantee that interference will not occur in a particular installation.

If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment to an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.



DARKGLASS is a registered trademark in the U.S., number 4,616,801, owned by Darkglass Electronics Oy.  
Designed by Revolve Studio