



Flex Focus Series

EXPERIENCE THE SOUND OF TRUE ENGAGEMENT

Vertical Line Array Solution for Longer Rooms

DESCRIPTION

The FF-V2.6 loudspeaker pairs use shaded line array technology with ribbon high frequency drivers to extend sound projection in longer rooms. Its frequency response (120 Hz - 20 kHz ± 3dB) is optimized for speech intelligibility and musical detail.

They are available in two configurations: FF-V2.6 for monitors that are mounted at a standard viewing height, and FF-V2.6 LAC (Lowered Acoustic Center) for monitors that are mounted above standard viewing height.

FF-V2.6 loudspeakers can be used in combination with an Innovox Micro-Sub Series subwoofer to extend low frequency response to support full-range music program.

KEY FEATURES

APPLICATIONS

- Made to match height of video display
- Precise 120° H x 25° V coverage pattern
- Line Array projection for longer rooms
- Stereo Video Conference speaker
- Audio to complement Digital signage
- 2.1 System in combination with MicroSub subwoofer



DESCRIPTIVE DATA

System Configuration:	Frequency-shaded line array Sold in pairs
Components & Loading:	(6) 3.5 " LF drivers; (1) HF ribbon
Enclosure Type:	Sealed enclosure, low profile column
Enclosure Material:	ABS with ABS endcaps
Connectors:	2-pole Phoenix
Suspension Options: (specify #1 or #2 when ordering)	#1 – Adjustable universal bracket for direct mount to display #2 – Wall-mount
Grille:	Integral, fabric wrapped

NOMINAL DATA

		120 Hz – 20 kHz ± 3 dB
Sensitivity:		95 dB @ 2.83V / 1M
		120° H x 25° V
Pattern Control to:		650 Hz
		8Ω
		200 W (AES-2)
Maximum Long-Term Output:		116 dB
Peak Output:		122 dB
Minimum Display Heig		37" / 940 mm
Dimensions		(custom)
		4.06" / 103 mm
	Depth:	2.13" / 54 mm
		14.0-31 lbs. / 3.7-14.1 kg
Approximate Shipping Weight:		18.0-35.0 lbs. / 8.2-15.9 kg

FF-V2.6 | FF- 2.6 LAC #innovox

Flex Focus™ Series

EXPERIENCE THE SOUND OF TRUE ENGAGEMENT

DIMENSIONAL DRAWINGS

