

CHS12LB50a

Battery Charging Station



- **Improved circuitry offers reduced charging time**
- **Charges up to 12 LB-50 Lithium Ion batteries**
- **Individual charging circuits and status indicators**

The CHS12LB50a battery charging station provides a convenient and organized means of recharging LB-50 batteries in larger systems with numerous batteries in regular use. The standard 19 inch, 1RU faceplate can be mounted in equipment racks for installations, in transit cases, or suitcases for mobile applications.

The unit is powered by external 5 VDC from the included DCR5/9AU power supply and AC cord appropriate for region of operation.

The battery charging station features an individual LED on each battery. Red indicates the battery is charging and green indicates the battery is completely charged.



DCR5/9AU



- Power requirements: 5VDC, 9A max.
DCR5/9AU power supply w/
AC cord appropriate for region
of operation (supplied)
- Battery charging time: 3.5 hours
- Dimensions: 19.00 in. wide
1.70 in. deep
1.97 in. high
- Weight:
With batteries: 2.15 lbs. (34.3 ozs.)
Without batteries: 1.55 lbs. (24.8 ozs.)



581 Laser Road NE • Rio Rancho, NM 87124 USA • www.lectrosonics.com
(505) 892-4501 • (800) 821-1121 • fax (505) 892-6243 • sales@lectrosonics.com



28 February 2022