



You deserve the Best

Introducing the new SR 350 IEM 



Introducing
the new SR 350 IEM G2

You deserve the Best



The **SR 350 IEM G2** is a twin transmitter with a high level of operational reliability and ease of use. Its unique diversity of features make it one of the best InEar transmitter you can get. The SR 350 IEM G2 twin transmitter consists of two stereo transmitters within one full rack space chassis and is compatible with the receivers EK 300 IEM G2 of the ew 300 IEM G2 Series and with EK 3253.

Technical Data

Modulation	Wideband, FM stereo
RF Output power	15 mW / 100 mW switchable
Frequency range	518 866 MHz
Switching bandwidth	36 MHz
Transmission- /receiving frequencies	1440
Presets	12 per bank, 8 write-protected banks and one configurable bank
Nominal/peak deviation	+/- 48 kHz
Noise reduction system	Sennheiser HDX
Signal-to-Noise ratio	> 91 dB(A)
THD (at nominal deviation and 1 kHz)	< 0,9%
Frequency Response	40 15,000 Hz
Antenna connector	2 x BNC
RF output	4 x XLR
Input voltage range	+ 10 dBu max
Powering	100 - 240 V
Dimensions	436 x 215 x 43 mm

- 1440 tunable UHF frequencies for interference-free reception
- rugged metal 19" housing
- user-friendly menu operation
- 2 headphone monitoring outputs
- Lock function avoids accidental changing of settings
- HDX compander for crystal-clear sound

In comparison to the SR 300 IEM G2 it offers the following additional advantages

- internal switching power supply
- switchable RF power: up to 100mW for an increased working range
- 19" chassis with pre-assembled rack ears