



LECTROSONICS IFB (INTERRUPTIBLE FOLD BACK) SYSTEM

Lectrosonics IFB systems are designed for use in broadcast and motion picture production to provide high-quality monaural audio for crew communications, program audio monitoring and talent cueing.

The IFBT4 frequency-agile transmitter has 256 UHF frequencies in 100kHz steps, 250mW RF output power, pilot tone squelch, and microprocessor control that provides user-friendly operation and eliminates transients at turn-on and turn-off. It also features a multi-use XLR input jack, and dip switch settings on the rear panel to provide direct compatibility with RTS and Clear Com® intercom systems. A preamp is also included in the input stage to allow direct connection to dynamic mics in "stand-alone" applications. Direct output at studio line level can also be fed directly into the transmitter. The IFBRIA beltpack receiver features an aluminum housing, preset frequency that can be set w/out power or transmitter signal, a scan mode that stores up to 5 additional frequencies, compander noise reduction, and up to 8hrs of life on a single 9V alkaline battery, or up to 20hrs via a single 9V lithium battery. The receiver will drive a variety of earbuds, headphones, or induction neck loops (not included) with 1/8" mini-plugs at levels with loads from 16ohms to 600ohms. Please specify frequency block, or call for assistance.

ITEM	DESCRIPTION	PRICE
IFBT4	Digital hybrid UHF IFB transmitter	CALL
IFBRIA	IFB beltpack receiver	CALL
BEZELKITRIA	Optional spring-loaded belt clip for IFBRIA beltpack	CALL
RMP195	4-channel rackmount for compact receivers or IFB transmitters	CALL



IFBT4



IFBRIA

TELEX



BTR24

TR24



TELEX BTR24/TR24 2.4GHZ WIRELESS INTERCOM The Telex® BTR-24 and TR-24 series intercom is a full-duplex (simultaneous talk and listen) wireless intercom system that offers a complete stand-alone solution for 2 to 10 users utilizing the full-duplex feature and an unlimited number of listen-only users. The BTR-24 system offers easy set-up, durable beltacks, 64-bit audio encryption, easy system expansion and a 3-year warranty. The Telex® BTR-24 system operates utilizing the license-free 2.4GHz IEEE 802.11b "WiFi" standard. The BTR-24 system incorporates the option of 3 audio channels that are selectable at each TR-24 beltack. The TR-24 beltacks also provide the user with adjustable volume control, headset microphone level, & local side tone level. The TR-24 will operate with dynamic or electret headset microphones & has a built-in lithium ion battery pack that will provide up to 8 hours on uninterrupted operation. Operating range of up to 800' (line-of-sight).

ITEM	DESCRIPTION	PRICE
BTR24	2.4GHz multi-channel base station, w/ omni antennas, rackmount & US power supply	1603.00
TR24	2.4GHz multi-channel wireless beltack with A4M headset conn, incl. US power supply	934.00
SYS243	System with carry case, 3 TR24, 1 BTR24, antennas, rack kits, power supply	CALL

TELEX

BELTPACK AND
HEADSET
SOLD SEPARATELY

NEW!

TELEX BTR-240 2.4GHZ WIRELESS INTERCOM SYSTEM Offering best-in-class audio performance, license-free operation, and an array of user-friendly features, wireless intercom has never been easier. This system features expanded coverage with BTR-24 access points, and the ability to use TR-240 belt packs as access points. The belt packs can operate wired or wireless. The system even auto-detects Electret or Dynamic microphones and adjusts accordingly. Up to 8 full-duplex beltacks and a virtually unlimited number of half-duplex beltacks may be used. Removeable Li-Ion batteries have a wide temperature range and offer up to 8 hours of operation. Other features include multi-level security and audio encryption, 2- and 4-wire interface options, ClearScan channel selection, choice of two independent or simultaneous audio channels, and an LCD display, as well as multiple antenna options and accessories.

ITEM	DESCRIPTION	PRICE
BTR-240-A4F-NA	2.4GHz wireless base station w/ A4F headset jack	3500.00
BTR-240-A4M-NA	As above, w/ A4M headset jack	3500.00
TR240-A4F-NA	2.4GHz beltack w/ A4F headset jack	885.00
TR240-A4M-NA	As above, w/ A4M headset jack	885.00



TELEX RADIOCOM™ BTR300 VHF WIRELESS INTERCOM SYSTEM

The BTR-300 VHF wireless intercom system is the first wireless intercom to be designed specifically with DTV band allocations in mind. Improved front end filtering allows the BTR-300 to be used in RF environments where other wireless intercoms simply can't function. The BTR-300 is compatible with wired AudioCom® and ClearCom® systems. Additional filtering capabilities and unique channel assignments allow up to four base stations and 16 individual beltacks to be used simultaneously.

ITEM	DESCRIPTION	PRICE
BTR300	VHF base station for up to (4) TR300's	3291.00
TR300	VHF remote transceiver, up to 4 per BTR300	979.00



TELEX RADIOCOM™ BTR700/BTR800 UHF SYSTEM Features include frequency-agile (synthesized) UHF operation, two intercom channels (BTR800 only, BTR700 is single intercom channel), stage announce output with relay closure (BTR800 only), wireless talk around (BTR800 only), ClearScan™ frequency auto-selection, 24 pre-programmed groups of intermod-free frequencies, talk/listen headset station, and easy-to-use graphics user interface. Up to 16 beltacks can be used in one location (four beltacks per base) and provide full duplex, 2-way communication. 100% ClearCom® compatible.

ITEM	DESCRIPTION	PRICE
BTR800	UHF base station	CALL
TR800	UHF beltack transceiver	1746.00
BTR700	UHF base station	CALL
TR700	UHF beltack transceiver	1334.00
TR825	Dual-listen belt pack	2570.00
BP800NM	NiMH battery pack only, for TR700/TR800	121.00
BC800NM4-301778400	Four-bay charger w/switching power supply and four battery packs	1356.00





ANCHOR AUDIO PROLINK 500 INTERCOM SYSTEM The ProLink 500 is a digital wireless intercom system that allows full-duplex communication between four users simultaneously with the option of an unlimited number of listen-only belt packs. The transmitter and receiver operate utilizing the FCC license-free 902-928MHz range for the U.S. without the need for a base station. The ProLink 500 has the capability to transmit up to 500' line-of-sight and allows communication through walls and glass. Depending on usage, it can operate up to 12 hours using rechargeable alkaline batteries. Each belt pack will be able to communicate in "Push-to-Talk" mode, which always receives but only transmits when the PTT button is pushed, or "Always On" mode providing hands-free communication. It has Bluetooth capability allowing the freedom to move around up to 10' from the MASTER belt pack.

ITEM	DESCRIPTION	PRICE
Packages		
PRO-540	ProLink package, (4) headsets, (1) master belt pack, (3) remote belt packs and (1) gang charger.....	3153.00
PRO-570	ProLink package, (7) headsets, (2) master belt packs, (5) remote belt packs, and (2) gang chargers.....	CALL

Individual Components

BP-500M	Master belt pack.....	569.00
BP-500R	Remote belt pack.....	569.00
H-2000	Dual earmuff headset.....	210.00
H-2000S	Single earmuff headset.....	210.00
GC-500	Gang charger.....	37.00
HC-ARMOR24-PL	Hard case - ProLink 500.....	310.00



HEADSETS
NOT INCLUDED

CLEAR-COM TEMPEST 2400/900 Frequency-hopping Spread Spectrum digital 2- and 4-channel wireless intercom operating in the 2.4GHz or 900MHz bands, designed to co-exist with WiFi, offering >94dB dynamic range, and high voice intelligibility. Supports unlimited users in Split and Shared Modes. In Normal Mode, up to 10 Base Stations and 5 full-duplex wireless Belt Stations can operate on one system with no frequency coordination required. No license fee required, 2-channel units listed, 4-channel versions also available.

ITEM	DESCRIPTION	PRICE
CM-222	2-channel base station, 2.4GHz.....	CALL
CM-922	2-channel base station, 900MHz.....	CALL
CP-222	2-channel dual-listen belt station, 2.4GHz.....	1435.50
CP-922	2-channel dual-listen belt station, 900MHz.....	1579.50



EARTEC®

NEW!

EARTEC COMSTAR FULL DUPLEX WIRELESS HEADSET SYSTEM

This system is designed specifically for teams that need to communicate while working with their hands. The self-contained headsets (no belt packs) are not voice activated and there is no delay when transmitting. Up to 8 users can speak simultaneously and communicate as they would on a traditional wired intercom system. Two groups of 4 users can communicate separately or all together in conference mode. It features an operating range of up to 800 yards. The system is self-tuning, without the need for a remote antenna. AC adapter, rechargeable battery (6 hour life) and AA disposable battery sled are included. It operates in the 1900MHz band which is reserved by the FCC for "PCS" voice communication only.



ITEM	DESCRIPTION	PRICE
COMSTAR-XT3	3-person intercom system with (1) dual-channel XT Series Com-Center, (2) single headsets, (1) double headset, (1) multiport charger and (1) carrying case.....	2350.00
COMSTAR-XT4	4-person intercom system with (1) dual-channel XT series Com-Center, (2) single headsets, (2) double headsets, (1) multiport charger, (1) carrying case.....	3000.00
COMSTAR-XT5	5-person intercom system with (1) dual-channel XT series Com-Center, (3) single headsets, (2) double headsets, (1) multiport charger, (1) carrying case.....	CALL
COMSTAR-XT6	6-person intercom system with (1) dual-channel XT series Com-Center, (3) single headsets, (3) double headsets, (1) multiport charger and (1) padded carrying case.....	CALL
COMSTAR-XT7	7-person intercom system with (1) dual-channel XT series Com-Center, (4) single headsets, (3) double headsets, (1) multiport charger, (1) padded carrying case.....	CALL
COMSTAR-XT8	8-person intercom system with (1) dual-channel XT series Com-center, (4) single headsets, (4) double headsets, (1) multiport charger, (2) padded carrying cases.....	CALL

EARTEC SIMULTALK 24G WIRELESS FULL DUPLEX TRANSCEIVER

For hands-free, short-range communications Simultalk 24G radios are a breakthrough. They operate in the 2.4GHz "non-licensed" frequency band and can be used anywhere in the world. They're field programmable and feature "dip switch" selectable frequency combinations. Everyone can receive the master unit, but only 1 receiver at a time can talk with the master unit. A full line of headset options allows each user to customize the transceivers for their own unique environment. The SLT-INT interface allows the Simultalk 24G system to be connected to a wired audio system.



ITEM	DESCRIPTION	PRICE
24G-4CYB	4-person setup, w/master radio, 3 remote radios, 4 cyber headsets, batteries, charger and case.....	540.00
ULTRA-SINGLE	Heavy-duty single-ear headset w/mic.....	123.50
DIG10XT	Super heavy-duty double-ear headset w/mic.....	214.50
TCSCYBEC	Lightweight single-ear headset w/mic.....	54.60
L024G	Single-ear headset, "The Loop".....	22.75
FN4XLR/F	Lightweight Fusion headset.....	67.20
PD4XLR/F	Midweight Proline Double headset, female connector.....	113.75
PD4XLR/M	As above, with male connector.....	113.75
SLT-INT	Interface for Simultalk 24G.....	212.50

EARTEC SC-1000 WIRELESS TRANSCEIVER This wireless transceiver operates in "Simplex" mode. When one person in a group transmits, the message is received by everyone. An unlimited number of transceivers can operate on the same frequency, and the system can also be used as a dual channel intercom with switching. SC-1000 transceivers feature a full watt of transmit power and a range of up to one mile. They use UHF high band frequencies that can penetrate concrete or steel. Other features include 16 UHF channel combinations, 38 privacy codes to block interference, a rugged polycarbonate body, military belt clip, and rechargeable NiCad battery.



ITEM	DESCRIPTION	PRICE
SC-1000	Wireless transceiver.....	123.50
SS900	Single muff headset.....	68.25
PS900	Single muff headset.....	100.10



Follow us!

We service many of the major brands that we carry.
Call our Authorized Repair Department at 800-356-5844 x1170.

Proven Intercom Systems



Tempest 2400



HME DX210



Clear-Com Encore Partyline

Highest Reliability for Demanding Productions.
Compact Designs with Comprehensive Capabilities.
Flexible Configurations Offer Maximum Control.

For over 40 years, Clear-Com's breadth of wired and wireless intercom systems has enabled critical communications of all size and complexity in Broadcast, Live Performance, House of Worship, Military, Aerospace and Government around the world. Our commitment to quality is unparalleled in the industry.

FULL COMPASS

PRO AUDIO | VIDEO | AV | LIGHTING
MUSICAL INSTRUMENTS

800-356-5844
FULLCOMPASS.COM



Clear-Com®
AN HME COMPANY



EARTEC®

EARTEC DIGICOM WIRELESS INTERCOM

Digicom uses microprocessor controlled transceivers engineered with a frequency-hopping architecture known as Spread Spectrum, which allows up to four people to communicate in full-duplex conversation simultaneously, and without need for a base station. To operate simply turn the units on and talk through the headsets, just like on a wired intercom. The STX1000 system affords a simultaneous talk, open-line talking pattern with a range up to 1/4 mile. It operates on rechargeable batteries with an 8-hour capacity. Includes batteries and wall charger. The DPX1000 is a wireless to wired interface that allows up to three Digicom remotes to communicate seamlessly in full-duplex with a wired network (Clear Com®, Telex®, PortaCom®, etc.). Each DPX-1000 package includes a Digicom master transceiver, software controlled interface module, remote antenna and XLR interconnect cable. No FCC license required.

ITEM	DESCRIPTION	PRICE
STX1000-MASTER	Digicom wireless intercom belt-pack transceiver (no headset).....	418.75
DPX1000	Interface to wired systems - specify which system you are using.....	783.13
DIG10PD	Double-muff headset for Digicom.....	130.00
DIG10PS	Professional single headset for Digicom.....	117.00
DIG10SS	Single headset for STX1000.....	97.50



HEADSET NOT INCLUDED

HME

HM ELECTRONICS DX100/DX100C WIRELESS INTERCOM SYSTEM

Clear, 2-way digital communications with a compact design for easy placement and operation. Up to 15 people can speak via headsets without interconnecting cables. Approved for worldwide use with 2.4GHz license-free operation and uses digital frequency-hopping spread spectrum technology to prevent "listening in". The base station can be powered by AA batteries, rechargeable BAT850 battery or power supply. All packages include mobile base station with 2 antennas, power supply, power cord, AA battery sled, and AC40A battery charger.

ITEM	DESCRIPTION	PRICE
DX100-CZ11383	DX100 system w/ 4 BP200 Belt-pacs, no headsets.....	CALL
DX100C-CZ11396	DX100C system w/ 4 ComLink WH200 wireless headset each w/ 2 batteries.....	CALL
DX100-CZ11433	DX100 system, w/ 4 BP200 Belt-pacs, 4 HS15 noise canceling headsets.....	CALL
DX100-CZ11445	DX100 system, w/ 3 BP200 Belt-pacs, 4 HS16 lightweight headsets.....	CALL
WS200-CZ11426	Wireless speaker station for DX100/DX200 base stations, includes built-in speaker, built-in electret mic, headset jack (4pin mini DIN type), selectable isolated or intercom channel, and front panel volume controls. Can be powered by 6 AA cells, 100-240 VAC, 12-14 VDC, or with optional BAT850 rechargeable battery system.....	1165.50

HM ELECTRONICS DX121/DX121C WIRELESS INTERCOM SYSTEM

This system can be plugged directly into the headset jack of any popular intercom system or four-wire device. Spectrum Friendly™ technology allows up to 8 DX121's to be used together to support multiple-channel applications. Compatible with all HME DX200 and DX100 series. It also features a built-in battery charger, selectable frequency range, and encryption technology to ensure confidential communication. All packages include a base station with HS-XLR4F cable, 2 antennas, power supply and cord.

ITEM	DESCRIPTION	PRICE
DX121-CZ11465	DX121 system w/ BP200 Belt-pac, no headsets included.....	2412.00
DX121C-CZ11464	DX121C system w/ ComLink WH200 wireless headset, 2 batteries.....	2434.50
DX121-CZ11462	DX121 system w/ 2 BP200 Belt-pacs, 1 HS15 noise canceling headset.....	2574.00
DX121-CZ11463	DX121 system w/ BP200 Belt-pac, 1 HS16 lightweight headset.....	2542.50
DX121-CZ11466	DX121 system w/ WS200 wireless speaker station.....	2875.50



HME

HM ELECTRONICS DX210 DIGITAL WIRELESS INTERCOM SYSTEM

Operating in the 2.4GHz band, this system delivers clear, interference-free audio. Its wired intercom interface is compatible with Clear-Com® or RTS 2-wire systems, and provides 2 separate 2- and 4-wire interconnections. In single channel mode, the IRU base station can support up to 16 full-duplex and 44 half-duplex belt-packs and/or wireless headsets by linking 4 base stations. It is paired with the BP210 belt-pack and various headsets (see line listings for package details.) Backwards compatible with the DX200 COMMUNICATOR models.

ITEM	DESCRIPTION	PRICE
DX210-CZ11513	DX210 system w/ (1) DX210 base station, (5) HS15 single muff headsets, (4) BP210 belt packs, (8) Li-ion batteries, (1) charger.....	CALL
DX210-CZ11514	DX210 system w/ (1) DX210 base station, (1) HS15 single muff headset, (4) WH210 wireless headsets, (8) Li-ion batteries, (1) charger.....	CALL
DX210-CZ11515	DX210 system with (1) DX210 base station, (4) BP210 belt packs, (8) Li-ion batteries, (1) charger [NO HEADSETS].....	CALL

**HM ELECTRONICS DX SERIES HEADSETS**

Headsets for use with the DX100/DX100C, DX121/DX121C, DX200/DX200C, and the DX300/DX300C.

ITEM	DESCRIPTION	PRICE
HS15-CZ11450	Single muff lightweight noise-canceling headset.....	164.70
HS15D-CZ11451	Double muff lightweight noise-canceling headset.....	274.50
HS16-CZ11452	Single muff lightweight with directional electret mic*.....	130.50
HS4-3-CZ11454	Earpiece & lapel (clip-on) electret mic*.....	76.50
WH200-CZ11392	ComLink wireless headset w/ 2 batteries, headstrap.....	724.50
WH300-CZ11407	All-In-One wireless headset w/ battery, headstrap.....	504.00
HS16000-CZ11453	2.5mm headset adapter for BP200 & BP300 Belt-pacs.....	74.70
MD-XLR4F-G27245-1	Adapter cable for XLR4F dynamic headset w/ BP200&300 belt-pacs, and WS200 speaker station.....	74.70
MD-XLR4F-G27256-1	Adapter cable for XLR4F dynamic headset w/ BP200&300 belt-pacs, and WS200 Speaker Station.....	74.70
MD-XLR5F-G27267-1	Adapter cable for CLR5M dynamic headset w/ BP200&300 belt-pacs, and WS200 Speaker Station.....	74.70
1156394	6' headset extension cable for HS14/14D, HS15/15D, HS16.....	9.90

*Not compatible with the DX300/DX300C series

WILLIAMS SOUND®
HELPING PEOPLE HEAR

WILLIAMS SOUND DIGI-WAVE DWS-COM6

With the push of a button, users can access hands-free, full-duplex digital communication up to 100' outdoors and up to 200' indoors. Any two mics can be live simultaneously. Operating on the 2.4GHz band with patented frequency-hopping software, it has a high resistance to RF interference. All controls are located on the front panel. The DLT-100 transceiver display shows current set-up, battery life, time, and RF strength. It also features a built-in microphone and speaker, and includes a charger with 14 hours of use per charge.

ITEM	DESCRIPTION	PRICE
DWS-COM6	Wireless intercom system - (6) DLT-100s, (6) MIC0442Ps, (6) CCS-044s and 1 system carry case.....	3228.30

Individual Components

DLT-100	Wireless digital transceiver.....	424.00
CCS-044	Silicone skin/wrist strap for the DLT-100.....	10.71
CHG-102	2-bay charger (for DLT-100).....	57.68



Follow us!

We have the largest selection of hard to find items. Call us!

DIGI·WAVE

WIRELESS INTERCOM

LIGHTS CAMERA INTERACTION

The *new* Digi-Wave™ Wireless Intercom System sets the stage for successful event production. Communicate clearly with crew members in multiple house locations in full-duplex mode. Accommodate any size production crew with any two mics live at one time. Enjoy hands-free operation with the quick push of a button. It's slim, lightweight and simple to set up and use. With Digi-Wave, the show will definitely go on.

Digi-Wave™ VIP Tour Guide systems also available... offering two-way Q&A capability.

Digi-Wave™ DWS-COM 6 PRO



WILLIAMS SOUND® | DIGI·WAVE™



800-356-5844
FULLCOMPASS.COM